

# प्रतिभूति कागज कारखाना, नर्मदापुरम-461005 ( म.प्र. )

( भारत प्रतिभूति मुद्रण तथा मुद्रा निर्माण निगम लिमिटेड की इकाई )

भारत सरकार के पूर्ण स्वामित्वाधीन

मिनीस्त्र श्रेणी - 1 सीपीएसई एवं आई.एस.ओ. 9001 : 2015, 14001:2015, 45001:2018, 50001:2018 एवं आईईसी 17025:2017 प्रमाणित

## SECURITY PAPER MILL, NARMADAPURAM - 461005 (M.P.)

(A Unit of Security Printing & Minting Corporation of India limited)

Wholly Owned by Government of India

Miniratna Category - I CPSE & ISO 9001 : 2015, 14001:2015, 45001:2018, 50001:2018 & IEC 17025:2017 Certified

CIN : U22213DL2006GOI144763, GSTIN : 23AAJCS6111J3ZE



Tel. No. 07574-255259, Fax No. : 07574-255170, E-mail : [gm.spm@spmCIL.com](mailto:gm.spm@spmCIL.com), Website : <http://spmnarmadapuram.spmCIL.com>

### शुद्धि पत्र / CORRIGENDUM - I

क्रमांक : 6000017692/Civil/

दिनांक : 03.10.2022

संदर्भ : पूछताछ क्रमांक 6000017692/Civil/705 दिनांक : 27.08.2022

Ref. : Tender Enquiry No. 6000017692/Civil/705 Date : 27.08.2022

उपरोक्त संदर्भित निविदा सूचना दिनांक 29.08.2022 को हमारी वेबसाइट <http://spmnarmadapuram.spmCIL.com> पर प्रकाशित की गई थी, जिसके संदर्भ में निम्नानुसार संशोधन करते हुए शुद्धि पत्र -1 जारी किया जा रहा है ।

Against our above tender enquiry was published in the <http://spmnarmadapuram.spmCIL.com> on dated 29.08.2022. Further, to this Corrigendum-I as below is being issued to the tender enquiry with the following amendments :

Sr. no.	Description	For	Read as
1.	Unit of Sr. No. 12 of Price Schedule	Cum	Kg
2.	<b>Section I :</b> Notice Inviting Tender	Date of sale of tender documents: From 29.08.2022 to 04.10.2022 during office hours. Closing Date and time for receipt of tenders - 04.10.2022 (15:00 hrs) Opening date and time of tenders : 04.10.2022 (15:00 hrs)	Date of sale of tender documents: From 29.08.2022 to 14.10.2022 during office hours. Closing Date and time for receipt of tenders - 14.10.2022 (15:00 hrs) Opening date and time of tenders : 14.10.2022 (15:00 hrs)

निविदा सूचना की अन्य सभी शर्तें यथावत रहेंगी ।

All other terms & condition of tender enquiry shall remain unaltered.

Sd/- 

प्रबंधक (सामग्री) / Manager (Material) 03/10/22

हेतु - मुख्य महाप्रबंधक / For- Dhief General Manager

ANNEXURE-I


Section XI: Price Schedule

TENDER NO. 6000017692/CIVIL/705 Dt. 27.08.2022

The Price bid should clearly indicate the break-up of the price as under:-

**GSTIN No. of your Firm :**

Sr. No.	Description	HSN	Qty	Unit	Rate	Amount
1	Earth work in surface excavation not exceeding 30 cm in depth but exceeding 1.5 m in width as well as 10 sqm on plan including getting out and disposal of excavated earth upto 50 m and lift upto 1.5 m, as directed by Engineer-in-Charge: All kinds of soil		170	Sqm		
2	Earth work in excavation by mechanical means (Hydraulic excavator) / manual means in foundation trenches or drains (not exceeding 1.5 m in width or 10 sqm on plan), including dressing of sides and ramming of bottoms, lift upto 1.5 m, including getting out the excavated soil and disposal of surplus excavated soil as directed, within a lead of 50 m. All kinds of soil		38	Cum		
3.	Excavating, supplying and filling of Murrum (including royalty) by mechanical transport upto a lead of 5km also including ramming and watering of the earth in layers not exceeding 20 cm in trenches, plinth, sides of foundation etc. complete.		35	Cum		
4.	Excavating holes more than 0.10 cum & upto 0.5 cum including getting out the excavated soil, then returning the soil as required in layers not exceeding 20cm in depth, including consolidating each deposited layer by ramming, watering etc, disposing of surplus excavated soil, as directed within a lead of 50 m		10	EA		

SECURITY PRINTING AND MINTING  
CORPORATION OF INDIA LIMITED

	and lift upto 1.5 m. All kinds of soil					
5.	Filling available excavated earth (excluding rock) in trenches, plinth, sides of foundations etc. in layers not exceeding 20cm in depth, consolidating each deposited layer by ramming and watering, lead up to 50 m and lift upto 1.5 m.		8	Cum		
6.	Providing and laying in position cement concrete of specified grade excluding the cost of centering and shuttering - All work up to plinth level: 1:4:8 (1 Cement : 4 coarse sand (zone-III) derived from natural sources : 8 graded stone aggregate 40 mm nominal size derived from natural sources).		20	Cum		
7.	Providing and laying in position specified grade of reinforced cement concrete, excluding the cost of centering, shuttering, finishing and reinforcement - All work up to plinth level : 1:1.5:3 (1 cement : 1.5 coarse sand (zone-III) derived from natural sources : 3 graded stone aggregate 20 mm nominal size derived from natural sources)		36	Cum		
8.	Reinforced cement concrete work in walls (any thickness), including attached pilasters, buttresses, plinth and string courses, fillets, columns, pillars, piers, abutments, posts and struts etc. above plinth level up to floor five level, excluding cost of centering, shuttering, finishing and reinforcement : 1:1.5:3 (1 cement : 1.5 coarse sand(zone-III) derived from natural sources : 3 graded stone aggregate 20 mm nominal size		15	Cum		



SECURITY PRINTING AND MINTING  
CORPORATION OF INDIA LIMITED

	derived from natural sources)					
9.	Reinforced cement concrete work in beams, suspended floors, roofs having slope up to 15° landings, balconies, shelves, chajjas, lintels, bands, plain window sills, staircases and spiral stair cases above plinth level up to floor five level, excluding the cost of centering, shuttering, finishing and reinforcement with 1:1.5:3 (1 cement: 1.5 coarse sand(zone-III) derived from natural sources : 3 graded stone aggregate 20 mm nominal size derived from natural sources).		9	Cum		
10	entering and shuttering including strutting, propping etc. and removal of form for					
10.1	Foundations, footings, bases of columns, etc. for mass concrete Qty:- 46 Sqm		46	Sqm		
10.2	Lintels, beams, plinth beams, girders, bressumers and cantilevers Qty:- 105 Sqm		105	Sqm		
10.3	Columns, Pillars, Piers, Abutments, Posts and Struts Qty:- 145 Sqm		145	Sqm		
11	Steel reinforcement for R.C.C. work including straightening, cutting, bending, placing in position and binding all complete upto plinth level and above plinth level Thermo-Mechanically Treated bars of grade Fe-500D or more.		7200	Kg		
12	Structural steel work in single section, fixed with or without connecting plate, including cutting, hoisting, fixing in position and applying a priming coat of approved steel primer and two coat of synthetic		2200	Kg		




SECURITY PRINTING AND MINTING  
CORPORATION OF INDIA LIMITED

	enamel paint of approved brand and manufacture to give an even shade :all complete.					
13.	Steel work in built up tubular (round, square or rectangular hollow tubes etc.) trusses etc., including cutting, hoisting, fixing in position and applying a priming coat of approved steel primer, including welding and bolted with special shaped washers etc. and Painting with synthetic enamel paint of approved brand and manufacture to give an even shade : all complete. Hot finished welded type tubes		5000	KG		
14.	52 mm thick cement concrete flooring with concrete hardener topping, under layer 40 mm thick cement concrete 1:2:4 (1 cement : 2 coarse sand : 4 graded stone aggregate 20 mm nominal size) and top layer 12 mm thick cement hardener consisting of mix 1:2 (1 cement hardener mix : 2 graded stone aggregate 6 mm nominal size) by volume, hardening compound mixed @ 2 litre per 50 kg of cement or as per manufacturer's specifications This includes cost of cement slurry, but excluding the cost of nosing of steps etc. complete.		160	Sqm		
15.	Providing and fixing glass strips in joints of terrazo/ cement concrete floors. 50 mm wide and 4 mm thick		346	Mtr		
16	Providing and fixing on wall face unplasticised Rigid PVC rain water pipes conforming to IS : 13592 Type A, including jointing with seal ring conforming to IS : 5382, leaving 10 mm gap for thermal expansion, (i) Single socketed pipes- 110 mm diameter		72	Mtr		



SECURITY PRINTING AND MINTING  
CORPORATION OF INDIA LIMITED

17	Providing and fixing on wall face unplasticised - PVC moulded fittings/ accessories for unplasticised Rigid PVC rain water pipes conforming to IS : 13592 Type A, including jointing with seal ring conforming to IS : 5382, leaving 10 mm gap for thermal expansion.					
17.1	17.1 Coupler 110 mm		12	EA		
17.2	Bend 87.5°- 110 mm		12	EA		
17.3	Shoe (Plain)-110 mm		12	EA		
18	Providing and fixing unplasticised -PVC pipe clips of approved design to unplasticised - PVC rain water pipes by means of 50x50x50 mm hard wood plugs, screwed with M.S. screws of required length, including cutting brick work and fixing in cement mortar 1:4 (1 cement : 4 coarse sand) and making good the wall etc. complete. 110 mm		36	EA		
19	Providing and fixing pre-coated galvanised iron profile sheets (size, shape and pitch of corrugation as approved by Engineer-in-charge) 0.50 mm (+ 0.05 %) total coated thickness with zinc coating 120 grams per sqm as per IS: 277, in 240 mpa steel grade, 5-7 microns epoxy primer on both side of the sheet and polyester top coat 15-18 microns. Sheet should have protective guard film of 25 microns minimum to avoid scratches during transportation and should be supplied in single length upto 12 metre or as		635	Sqm		



SECURITY PRINTING AND MINTING  
CORPORATION OF INDIA LIMITED

	desired by Engineerin- charge. The sheet shall be fixed using self-drilling /self-tapping screws of size (5.5x 55 mm) with EPDM seal, complete upto any pitch in horizontal/ vertical or curved surfaces, excluding the cost of purlins, rafters and trusses and including cutting to size and shape wherever required.					
20	Providing and fixing pre-coated galvanised steel sheet roofing accessories 0.50 mm (+0.05 %) total coated thickness, Zinc coating 120 grams per sqm as per IS: 277, in 240 mpa steel grade, 5-7 microns epoxy primer on both side of the sheet and polyester top coat 15-18 microns using self-drilling/ self-tapping screws complete :					
20.1	Ridges plain (500 - 600mm)		18	Mtr		
20.2	Gutter (600 mm over all girth)		36	Mtr		
21	Extra for providing and fixing wind ties of 40x 6 mm flat iron section.		72	Mtr		
22	6 mm cement plaster of mix : 3 (1 cement: 3 fine sand)		365	Sqm		
23	Finishing walls with Acrylic Smooth exterior paint of required shade :					
	New work (Two or more coat applied @ 1.67 ltr/10 sqm over and including priming coat of exterior primer applied @ 2.20 kg/10 sqm)		365	Sqm		
24	Boring, Providing and installing cast in situ single under reamed piles of specified diameter and length below pile cap in M-25 cement concrete, to carry a safe					



SECURITY PRINTING AND MINTING  
CORPORATION OF INDIA LIMITED

	working load not less than specified, excluding the cost of steel reinforcement but including the cost of boring with bentonite solution and the length of the pile to be embedded in pile cap etc. all complete. (Length of pile for payment shall be measured upto to the bottom of pile cap)					
	300 mm dia pile		102	Mtr		
25	Total					
26	Any other charges (if any)					
27	Total					
28	Total GST amount					
29	<b>Total</b>					
30	Total Price (F.O.R, SPM, HOSHANGABAD) (in figures only) (46+47)					
31	Total Price (F.O.R, SPM, HOSHANGABAD) (in words only)					

Note :-The method of evaluation of L1 criteria for awarding the contract shall be decided taking into consideration the total landed price up to SPM Narmadapuram.

Signature.....

Name.....

Designation .....

Date .....