


प्रतिभूति कागज कारखाना, नर्मदापुरम-461005 (म.प्र.)

(भारत प्रतिभूति मुद्रण तथा मुद्रा निर्माण निगम लिमिटेड की इकाई)

भारत सस्कार के पूर्ण स्वामित्वाधीन





SECURITY PAPER MILL, NARMADAPURAM - 461005 (M.P.)

(A Unit of Security Printing & Minting Corporation of India limited)

Wholly Owned by Government of India

Miniratna Category - I CPSE & ISO 9001: 2015, 14001:2015, 45001:2018, 50001:2018 & IEC 17025:2017 Certified

CIN: U22213DL2006GOI144763, GSTIN: 23AAJCS6111J3ZE

Tel. No. 07574-255259, Fax No.: 07574-255170, E-mail: gm.spm@spmcil.com, Website: http://spmnarmadapuram.spmcil.com

NOTICE INVITING TENDER

Tender No. 6000017712/Civil/700,

Dated: 29.08.2022

E-tenders are invited from eligible bidders for "Construction of Ladies Toilet with false ceiling on Visitor Room". All the details regarding tenders are available at our SPM website https://www.spmnarmadapuram.spmcil.com and MSTC website http://www.mstcecommerce.com/eproc/. In future corrigendum/extension etc., if any, shall be published only on website https://www.mstcecommerce.com/eproc/.

Further event details available on MSTC website (https://www.mstcecommerce.com/eproc/) is as below:

Buyer	Category
SECURITY PAPER MILL, NARMADAPURAM	WORKS

Event Number	Description Event	Last Date
SPMCIL/Security Paper Mill Narmadapuram/Purchase/15/22-23/ET/178	"Construction of Ladies Toilet with false ceiling on Visitor Room"	07.10.2022 15:01 Hrs

SD/-Manager (Material) SPM, Narmadapuram

Vendor Registration Procedure for Common Portal(V3) e-Procurement

System Requirements:

- 1. OS Windows 10 and above, browser Internet Explorer 10 and above
- 2. Digital Signature Class 3 and above (both signing and encrypting)

STEPS:

- 1. Please visit https://www.mstcecommerce.com
- 2. Scroll onto e-Procurement tab and click on "Common Portal"
- 3. In the Vendor Login, please click on "Register"
- 4. Please fill all the details and follow the onscreen form to get registered.
- 5. Click on Submit button.
- 6. After the successful registration, an automated confirmation e-mail is sent to the provided email address.

Post Submission Login using your Digital Signature Class 3(both signing and encryption)

For System Settings:

MSTC Help Desk Ph. 033 23400020, 23400021, 23400022

For System Settings Video Tutorial open link: bit.ly/v3mstcvid



SECURITY PAPER MILL, NARMADAPURAM - 461005 (M.P), INDIA

(A Unit of Security Printing and Minting Corporation of India Limited) (Wholly owned by Government of India)

(Miniratna Category-I CPSE & ISO 9001:2015 & ISO 14001:2015 CERTIFIED)

Website: http://spmnarmadapuram.spmcil.com

E-Mail:gm.spm@spmcil.com

CIN: U22213DL2006GOI144763 GSTIN: 23AAJCS6111J3ZE Ph.No:91-7574-255259, Fax No: 07574-255170

PR Number	PR Date	Indenter	Department
12004344	02.06.2022	CSKHATARKAR	CIVIL WING

Not Transferable

Security Classification: .	
----------------------------	--

TENDER DOCUMENT FOR: CONSTRUCTION OF LADIES TOILET ALONG WITH FALSE CEILING ON VISITOR ROOM

Tender No: 6000017712/CIVIL/22-23/700 Dated: 27.08.2022

This Tender Document Contains _70 _ Pages.

Tender Documents is issued to:

M/s	

Details of Contact person in SPMCIL regarding this tender:

Name, Designation: Vikas Kumar (Manager (Material)

Address: SPM5 (PM5, SPM Narmadapuram)

Phone, Fax, email: 07574-286842

Email: vikas.kumar@spmcil.com



Section I: Notice Inviting Tender (NIT)

Tender Sl. No. 6000017712/CIVIL/700 , Dated: 27.08.2022

1 Sealed tenders are invited from eligible and qualified tenderers for supply of the following:

Schedul e No.	Brief Description of Goods/ services	Quantity (with unit)	Earnest Money (in Rs.)	Remarks
01	C/o ladies toilet & renovation work	1.000 AU	17000.00INR	
02	P/F false ceiling	1.000 AU		

Type Of Tender (Two Bid/ PQB/ EOI/ RC/ Development/ Indigenization/ Disposal of Scrap/ Security Item etc.)	TWO-BID NATIONAL COMPETETIVE BID	
Dates of Sale of Tender documents	As per MSTC E-Procurement Portal	
Place of sale of tender documents	As per MSTC E-Procurement Portal	
Closing date and time for receipt of tenders	As per e-procurement on MSTC.	
Place of receipt of tenders	On MSTC E-procurement Portal	
Time and date of opening of tenders	As per e-procurement on MSTC.	
Place of opening of tenders	ADM OFFICE SECURITY PAPER MILL NARMADAPURAM	
Nominated Person/ Designation to Receive Bulky Tenders (Clause 21.21.1 of GIT)	VIKAS KUMAR , MANAGER(MATERIAL)	

- 2 Eligibility to participate as per Government of India's Public Procurement (Preference to Make in India) Order 2017 (as amended/ revised) and Ministry of Finance, Department of Expenditure, Public Procurement Division's Orders (Public Procurement 1, 2 and 3) F.No.6/18/2019-PPD dated 23rd/ 24th July 2020 (or any further amendments thereof) regarding eligibility of bidders from neighboring countries shall apply to this tender.
- 3 Please note that SPMCIL reserves its right to grant Purchase preferences in accordance with Government of India's Public Procurement (Preference to Make in India) Order 2017 (as amended/ revised) and Public Procurement Policy for Micro and Small Enterprises (MSEs) Amendment Order, 2018 (as amended/ revised).
- 4 Interested tenderers may obtain further information about this requirement from https://www.mstcecommerce.com/eproc/.
- 5 Tenderer may also download the tender documents from the web site https://spmnarmadapuram.spmcil.com/ or https://www.mstcecommerce.com/eproc/ and submit its tender by utilizing MSTC E-procurement Portal.
- 6 Tenderer may also download the tender documents from the web site mentioned above and submit its tender by utilizing the downloaded document; the bidder must not make any changes to



the contents of the documents, except for filling the required information. A certificate to this effect must be submitted by the bidder in the Tender Form (Section X).

- 7 Tenderers shall ensure that their tenders, duly sealed and signed, complete in all respects as per instructions contained in the Tender Documents, are to be submitted on MSTC Govt. e-procurement portal and the website is https://www.mstcecommerce.com/eproc/.
- 8 In the event of any of the above-mentioned dates being declared as a holiday/ closed day for the purchase organization, the tenders will be sold/ received/ opened on the next working day at the appointed time.
- 9 The tender documents are not transferable.
- The bidder, their affiliates, or subsidiaries including subcontractors or suppliers for any part of the contract – should not stand declared ineligible/ blacklisted/ banned/ debarred by any Government Agency anywhere in the world, for participating in its tenders, under that country's laws or official regulations. A declaration to this effect shall be submitted by the bidder in the Tender Form (Section X).
- 11. EMD amount mentioned in Section VI List of Requirements shall be furnished in any one of the following forms:
 - a) Account Payee Demand Draft
 - b) Fixed Deposit Receipt
 - c) Banker's cheque

In acceptable form, otherwise the tender will not be accepted in any case. The demand draft, fixed deposit receipt or banker's cheque shall be drawn on any scheduled commercial bank in India, in favour of account and place of payment specified in the para 1 above. In case of bank guarantee, the same is to be provided from/confirmed by any scheduled commercial bank in India as per the format specified under section XIII in these documents.

Bidder has to upload scanned copy / proof of the DD along with bid and has to ensure delivery of hardcopy to the Buyer within 5 days of Bid End date / Bid Opening date.

- 12. Enclosed: BIDDER'S CHECK LIST BEFORE TENDER SUBMISSION
- 1. Price Schedule (Annexure-I)
- 2. Check list (Annexure-II)
- 3. Declaration (Annexure-III)
- 4. Declaration (Annexure-IV)
- 5. Declaration (Annexure-V)
- 6. Confidentiality and non-disclosure agreement.



Yours faithfully,

(Vikas Kumar) Manager(Purchase) For Chief General Manager

E-mail: <u>vikas.kumar@spmcil.com</u> PHONE:- (07574) 286842 & 286588

CORRESPONDING ADDRESS

THE CHIEF GENERAL MANAGER SECURITY PAPER MILL NARMADAPURAM-461005(M.P.)

SIGNATURE OF BIDDER W DESIGNATION & SEAL	ITH NAME ,
[Name, designation, addr For and on behalf of	ess, tel. No etc. of the officer signing the document]



Section II: General Instructions to Tenderer (GIT) Part I: General Instructions Applicable to all Types of Tenders



SIGNATURE OF BIDDER WITH NAME, DESIGNATION & SEAL



Section II: General Instructions to Tenderer (GIT) Part II: General Instructions Applicable to all Types of Tenders



SIGNATURE OF BIDDER WITH NAME, DESIGNATION & SEAL



Section III: Special Instructions to Tenderers (SIT)

The following Special Instructions to Tenderers will apply for this purchase. These special instructions will modify/ substitute/ supplement the corresponding General Instructions to Tenderers (GIT) incorporated in Section II. The corresponding GIT clause numbers have also been indicated in the text below:

In case of any conflict between the provision in the GIT and that in the SIT, the provision contained in the SIT shall prevail.

(Clauses of GIT listed below include a possibility for variation in their provisions through SIT. There could be other clauses in SIT as deemed fit.)

SI. No.	GIT Clause No.	Topic	SIT Provision
1	3.	Eligible Tenderers	Applicable
2	3.4	Eligible Goods and Services (Origin of Goods)	Applicable
3	6.1	The tender documents includes:	Applicable
4	8	Pre-bid Conference	Not Applicable
5	9	Time Limit for receiving request for clarification of Tender Documents	A Tenderer requiring any clarification or elucidation on any issue of the tender documents may take up the same with SPMN in writing or by fax/e-mail/telex. SPMN will respond in writing to such request provided the same is received before 14 days prior to the prescribed date of submission of tender.
6	10.1	The Technical bid to be submitted by Tenderer shall contain the following documents, duly filled in, as required:	Applicable
7	11.2	Tender Currency	Supplier is requested to quote price in INR within 2 Decimal place. Quotation with price quote beyond 2 decimal place is ignored.
8	12.1	Tender Prices	Applicable
9	12.2,33,3 6.1	Schedule wise evaluation	Not Applicable
10	12.6	GST details	Applicable
11	14	PVC Clause & Formula	Not Applicable
12	14.4 to 14.7	Exchange Rate Variation (ERV)	Not Applicable
13	16.1 a) to c)	Documents Establishing Tenderer's Eligibility and Qualifications	Not Applicable



14	18.4, 18.5	Earnest Money Deposit (EMD)	@ 2% i.e. Rs.17,000
15	19	Tender Validity	120 DAYS FROM THE DATE OF OPENING OF BID
16	20.4	Number of Copies of Tenders to be submitted	One copy in original
17	20.8	Two Bid System	Applicable.
18	20.9	E-Procurement	Applicable
19	34. and 35.1	Comparison on CIF Destination Basis	Not Applicable
20	35.2 to 35.6	Additional Factors for Evaluation of Offers and Preferential schemes	Not Applicable
21	43	Parallel Contracts	Not Applicable
22	44.1	Serious Misdemeanors	Applicable
23	44.3	Integrity Pact	Not Applicable
24	45.1	Notification of Award	Applicable
25	50.	Applicability of additional GIT for rate Contracts	Not Applicable
26	51.	Applicability of additional GIT for PQB Tenders	Not Applicable
27	52.	Applicability of additional GIT for Tenders involving Samples	Not Applicable
28	53.	Applicability of additional GIT for EOI Tenders	Not Applicable
29	54.	Applicability of additional GIT for Tenders for Disposal of Scrap	Not Applicable
30	55.	Applicability of additional GIT for Development/Indigenization Tenders	Not Applicable
31	Special Condition	GST Returns	Supplier Should file the GST returns in time. SPM reserves the right to withhold the payment of GST till production of evidence of filling of Returns.
32	Special Condition	TCS u/s 206C (1H) read with TDS u/s 194Q:	SPM (as Buyer) is liable to deduct TDS u/s 194Q @ applicable rate on goods purchases (if applicable). In case of deduction of TDS under section 194Q; the Supplier (Vendor) need not to charge TCS u/s 206C (1H) on invoicing on or after 01.07.2021.
33	Special Condition	Sec. 206AB of IT Act:	Vendor has to submit declaration in specified format for the compliance of Section 206AB of Income Tax Act, 1961. In case of non-submission of declaration; TDS will be deducted at higher rates (as applicable) as per section 206AB.



Section IV: General Conditions of Contract (GCC) Part I: General Conditions of Contract applicable to all types of Tenders

Kindly refer https://spmcil.com/uploaddocument/GCC/new.pdf for further details (GIT contains 36 pages).



Section IV: General Conditions of Contract (GCC) Part II: Additional General Conditions of Contract applicable to all types of Tenders

Kindly refer https://spmcil.com/uploaddocument/GCC/new.pdf for further details (GIT contains 36 pages)



Section V: Special Conditions of Contract (SCC)

The following Special Conditions of Contract (SCC) will apply for this purchase. The corresponding clauses of General Conditions of Contract (GCC) relating to the SCC stipulations have also been incorporated below. These Special Conditions will modify/ substitute/ supplement the corresponding (GCC) clauses.

Whenever there is any conflict between the provision in the GCC and that in the SCC, the provision contained in the SCC shall prevail.

(Clauses of GCC listed below include a possibility for variation in their provisions through SCC. There could be other clauses in SCC as deemed fit)

S. No.	GCC Clause No.	Topic	SCC Provision
1	1.2	Abbreviations:	APPLICABLE
2	6.1, 6.3 & 6.5	Performance Bond/ Security	REFER SECTION-VI, CLAUSE NO.5 OF THE TENDER ENQUIRY)
3	8.2	Packing and Marking	NOT APPLICABLE
4	9	Inspection and Quality Control	NOT APPLICABLE
5	11.2	Transportation of Domestic Goods	APPLICABLE
6	12.	Insurance	APPLICABLE
7	15	Distribution of Dispatch Documents for clearance/ Receipt of Goods	APPLICABLE
8	16.2, 16.4	Warrantee Clause	REFER SECTION-VI, CLAUSE NO.6 OF THE TENDER ENQUIRY)
9	19.3	Option Clause	The General Manager Security Paper Mill Narmadapuram may reserve the right to increase the ordered quantity by 25% at any time, till final delivery date of the contract, by giving reasonable notice even though the quantity ordered initially has been supplied in full before the last date of Delivery Period.
10	20.1	Price Adjustment Clause	NOT APPLICABLE
11	21.	Taxes and Duties	APPLICABLE
12	22.	Terms and Mode of payments	REFER SECTION-VI, CLAUSE NO.4 OF THE TENDER ENQUIRY)
13	24.1	Quantum of LD	If the contractor fails to deliver the goods and/or services or any installment thereof within the Delivery Period, SPM Narmadapuram shall, without prejudice to other rights and remedies available to SPM, Narmadapuram under the contract, deduct from the contractor price, as Liquidated damages, a sum equivalent to the rate of 0.5 % of the delivered price of the delayed goods and/or services along with applicable GST of



			18% on the LD amount, for each week of delay or part thereof until actual delivery or performance, subject to a maximum deduction of the 10% (plus GST on the LD amount) of the delayed goods or services.
14	25.1	Bank Guarantee and Insurance for Material Loaned to Contractor	Not Applicable
15	33.1	Resolution of Disputes	APPLICABLE
16	36.3.2,	Disposal/ Sale of Scrap by Tender	Not Applicable



Section VI: List of Requirements

Sche	Brief description of goods	HSN	Accounting	Quantity	Amount of	Place	of
dule	and services (Related	Code	unit		Earnest	Delivery 1	for
No.	specifications etc. are in				Money	GST	
	Section-VII)				(INR)	purpose	
1	C/o ladies toilet & renovation		AU	1.00	18000.00INR		
2.	P/F false ceiling		AU	1.00			

Technical bid and financial bid are to be submitted on the MSTC E-Procurement Portal. It may be noted that the price is not to be quoted either in technical bid(Technical Cover). It shall only be quoted in price bid(Price Cover). Non-adherence to this shall be making tender liable for rejection.

Tenders shall be submitted in parts as below:-

SUBMISSION OF TENDER: The bid is to be submitted in two parts are as follows:

- I. PART-A: TECHNO-COMMERCIAL BID: KINDLY SUBMIT FOLLOWING DOCUMENTS WITH TECHNO-COMMERCIAL BID:
- (1). Tender Fee: NOT Applicable
- (2). (i) Earnest Money Deposit: Applicable and Bidder has to upload scanned copy / proof of the DD along with bid and has to ensure delivery of hardcopy to the Buyer within 5 days of Bid End date / Bid Opening date.
 - (ii) MSME firm submit valid MSME Certificate containing the tendered item in store list.
- (3) Power of Attorney/ Authorization with the seal of the company of person signing the tender documents.
- (4) Containing un-priced tender consisting commercial package including all terms and conditions. No price details to be given in this tender (as per Section-X).
- (5) The tenderer shall submit the acceptance of detailed scope of work as per Section VII of this tender document.
- (6) Blank price bid duly sealed and signed without mentioning any price element.
- (7) Please confirm the validity, place of work, contract period and payment terms as per the other terms and condition (point no.1 to 4) of Section VI of tender document.
- (8) Submit the following declaration on your letter head with seal and sign as per the Annexure III of this tender:
- a. We have not been blacklisted / debarred by BNPMIPL/BRBNMPL/SPMCIL or any Govt. Departments for participation in tenders. The information provided above is correct and true to the



best of my knowledge and belief.

- b. We do hereby declare that we have read and understood all terms and conditions of tender document including GIT,SIT, GCC, SCC, Technical Specification, Quality Control Criteria and confirm to abide to those conditions without any counter conditions.
- c. "We are accepting all the terms and conditions of the tender document without any deviation and withdraw all deviations if any"
- (9) All Section & pages (front and back) of the tender documents strictly should be signed, name and sealed by bidder firm.
- (10) Submit the declaration duly seal and signed by Competent Authority on your letter head as per section-IX: Qualification/Eligibility criteria point no. VI (as per annexure-IV) as below:
- "I have read the clause regarding restrictions on procurement from a bidder of a country which shares a land border with India: I certify that M/s.....(firm's name) is not from such a country or, if from such a country, has been registered with the Competent Authority. I hereby certify that M/s(firm's name) fulfills at requirements in this regard and is eligible to be considered."
- I, the undersigned, declare that the item.....originate in.....(Name of the country).
- II. PART B: PRICE BID:

The bidders shall quote the price and other elements of price as per the format given as Section – XI of this tender documents. Insertion, post script, addition and alteration shall not be made, if any, will not be considered for calculating the price.

Note:

- 1. Un- Workable rates shall be liable for rejection.
- 2. "BIDDER TO FURNISH STIPULATED DOCUMENTS ALONG WITH TENDER IN SUPPORT OF FULFILLMENT OF TENDER CRITERIA. FURTHER CORRESPONDENCE IN THIS REGARD WILL NOT BE ENTERTAINED FOR ANY REASON. NON-SUBMISSION OR INCOMPLETE SUBMISSION OF DOCUMENTS MAY LEAD TO REJECTION OF OFFER
- 3. Non submission of any of the above document may lead to rejection of bid.

OTHER IMPORTANT TERMS AND CONDITIONS:

- (1). Validity: 120 days from the date of opening of the tender, offer valid for a shorter period shall be treated as unresponsive & rejected.
- (2). Place of work: Security Paper Mill, Narmadapuram
- (3). Required completion period of work :- 05 months after issue of NAC / PO.
- (4) TERMS AND MODE OF PAYMENT:
- a. 100% payment shall be made as based on actual measurement of completed work/items after completion, suitability and on production of all required documents.
- b. The payment will be made by SPM through RTGS / NEFT to the contractor after submission of their bill duly certified by CIVIL DEPARTMENT.



- c. Applicable taxes may please mention on Price schedule/ Invoice of document along with HSN/ SAC code.
- d. Registration certificate of GSTIN issued from the concerned authority may please be attached along with tender document.
- e. If income tax is payable then the bill payment will be made after the deduction of such taxes. The TDS certificate will be provided to the Contractor accordingly. The contractor will provide PAN in bills.
- f. Any TDS or surcharge applicable to the contractor then as per rule the deduction from the bill will be made along with surcharge. The copy of the same will be provided accordingly.

(5) PERFORMANCE SECURITY

- (5.1) Within twenty-one days after the issue of notification of award by SPMN, the supplier shall furnish performance security of the value equal to 03% of the value of the contract to SPMN, valid up to sixty days after the date of completion of all contractual obligations by the supplier, including the warranty obligations.
- (5.2) The performance security shall be denominated in Indian Rupees or in the currency of the contract and shall be in one of the following forms:
- (a) Account payee Demand Draft or Fixed Deposit Receipt drawn on any commercial bank in India, in favour of Security Paper Mill, Narmadapuram as indicate in the clause 3 of NIT.
- (b) Bank Guarantee issued by a commercial bank in India, in the prescribed form as provided in Section XV of this document.
- (5.3) In the event of any loss due to supplier's failure to fulfill its obligations in terms of the contract, the amount of the performance security shall be payable to SPM to compensate SPM for the same.
- (5.4) In the event of any amendment issued to the contract, the supplier shall, within twenty-one days of issue of the amendment, furnish the corresponding amendment to the Performance Security (as necessary), rendering the same valid in all respects in terms of the contract as amended.

(6) WARRANTY:

- i. The supplier warrants that the goods supplied under the contract is new, unused and incorporate all recent improvements in design and materials unless prescribed otherwise by SPM in the contract. The supplier further warrants that the goods supplied under the contract shall have no defect arising from design, materials (except when the design adopted and / or the material used are as per SPM's specifications) or workmanship or from any act or omission of the supplier, that may develop under normal use of the supplied goods under the conditions prevailing in India.
- ii. This warranty shall remain valid for twelve months after the goods or any portion thereof as the case may be, have been delivered to the final destination and installed and commissioned at the final destination and accepted by SPM in terms of the contract or for eighteen months from the date of dispatch from the supplier's premises whichever is later.
- iii. In case of any claim arising out of this warranty, SPM shall promptly notify the same in writing to the supplier.
- iv. Upon receipt of such notice, the supplier shall, with all reasonable speed and time, repair or replace the defective goods or parts thereof, free of cost, at the ultimate destination. The supplier



shall take over the replaced parts/ goods after providing their replacements and no claim, whatsoever shall lie on SPM for such replaced parts/ goods thereafter.

v. In the event of any rectification of a defect or replacement of any defective goods during the warranty period, the warranty for the rectified/ replaced goods shall be extended to a further period of twelve months from the date such rectified / replaced goods starts functioning to the satisfaction of SPM.

vi. If the supplier, having been notified, fails to rectify/ replace the defect(s) within a delivery period, SPM may proceed to take such remedial action(s) as deemed fit by SPM, at the risk and expense of the supplier and without prejudice to other contractual rights and remedies, which SPM may have against the supplier.

7. Procurement Preference for MSE

- (i) From time to time, the Government of India (GoI) lays down procurement policies to help inclusive national economic growth by providing long-term support to small and medium enterprises and disadvantaged sections of society and to address environmental concerns. The Procurement Preference Policy for Micro and Small Enterprises has been notified by GoI4 in exercise of the powers conferred in Section 11 of the Micro, Small and Medium Enterprises Development (MSMED) Act, 2006.
- (ii) Micro and Small Enterprises (MSE) must, along with their offer, provide proof of their being registered as MSE (indicating the terminal validity date of their registration) for the item tendered, with any agency mentioned in the notification of the Ministry of Micro, Small and Medium Enterprises (MSME), indicated below:
- (a) District Industries Centres.
- (d) Khadi and Village Industries Commission.
- (e) Khadi and Village Industries Board.
- (f) Coir Board.
- (g) National Small Industries Corporation.
- (h) Directorate of Handicraft and Handloom; and
- (i) Any other body specified by the Ministry of MSME.
- (iii) For ease of registration of Micro and Small Enterprises (MSEs), Ministry of MSME has started Udyog Aadhar Memorandum which is an online registration system (free of cost) w.e.f. 18th September 2015 and all Micro & Small Enterprises (MSEs) who are having Udyog Aadhar Memorandum should also be provided all the benefits available for MSEs under the Public Procurement Policy for Micro and Small Enterprises (MSEs), Order 2012.
- (iv) The MSEs are provided tender documents free of cost and are exempted from payment of earnest money, Subject to furnishing of relevant valid certificate for claiming exemption.
- (v) As per MSME Act, 2006 and Government of India's stimulus package announced on 13/02/2020 MSME payments have to be released within 45 days by Government and PSUs. As per the MSME Act, delays may attract punitive interest.
- (vi) Under Public Procurement Policy for MSEs, a minimum 255 per cent share out of the total procurement by Central Government Ministries/ Departments/ Public Sector Undertakings are to be made from MSEs. To meet this target, PSUs are required to conduct special Vendor Development Programmes/ Buyer-Seller Meets for SCs/STs entrepreneurs.



(vii) If a MSE bidder quotes a price within the band of the lowest (L1) +15 per cent in a situation where the L1 price is quoted by someone other than an MSE, the MSE bidders are eligible for being awarded 25 per cent of the total tendered value if they agree to match the L1 price. In case of more

than one such eligible MSE, the 25 per cent quantity is to be distributed proportionately among these bidders. Within this, a purchase preference of 4 per cent is reserved for MSEs owned by Scheduled Caste (SC)/ Scheduled Tribe (ST) entrepreneurs and 3 per cent is reserved for procurement from MSEs owned by women (if they participate in the tender process and match the L1 price). Provided that, in event of failure of such SC/ ST or Women MSE to participate in tender

process or meet tender requirements and L1 price, 4 percent sub-target shall be met from other MSE. MSEs would be treated as owned by SC/ ST or women entrepreneurs:

- (a) In case of proprietary MSE, proprietor(s) shall be SC /ST or women
- (b) In case of partnership MSE, the SC/ ST or women partners shall be holding at least 51% shares in the unit
- (c) In case of Private Limited Companies, at least 51% share shall be held by SC/ ST or women promoters.

In the opinion of Ministry of MSME, in case of tender item is non-split-able or non-dividable, etc. MSE quoting price within price band L1+15% may be awarded for full/ complete supply of total tendered value to MSE, considering spirit of policy for enhancing the Govt. procurement from MSE.

This Policy is meant for procurement of only goods produced and services rendered by MSEs and not for any trading activities by them. An MSE Unit will not get any purchase preference over another MSE Unit.

NOTE: As per MSME office Memorandum No. F.No.1(3)/2018-MP, Part-III dated 25.03.2022. Subjected "Revised FAQs in respect of Public Procurement Policy for MSEs Order, 2012 reg.FAQ Question No.18 the works contracts are excluded from the purview of Public Procurement policy of MSME order 2012."

(8) SCHEDULE WISE EVALUATION

The Evaluation of L1 bidder shall be based on the consolidated Grand total offered by the bidder as per section - XI of this tender document

- (9) Any dispute, arising out of the supply order/ contract will be subject to the exclusive jurisdiction of the competent court at Hoshangabad.
- (10) Authorized representatives of the tenderers, who have submitted tenders on time may attend the tender opening, provided they bring with them letters of authority through firm.
- (11) All Sections & pages of the tender documents strictly should be signed, name and sealed by bidder firm.

Note:

2. OTHER TERMS AND CONDITIONS

The Contractor must fulfill all the provisions/conditions required under the following Acts;

- 1. The Contract Labour (Regulation & Abolition) Act, 1970.
- 2. The Minimum Wages Act, 1948
- 3. The Payment of Wages Act, 1936



- 4. The Employee Provident Fund & Misc. Provisions Act, 1936
- 5. The Employee Estate Insurance Act, 1948.
- 6. The Industrial Dispute Act, 1947
- 7. The Employees Compensation Act, 1923
- 8. The Payment of Bonus Act.
- 9. Other Misc. as & when Applicable

(12) Safety Conditions:

- 12.1 The manpower supplied by the contractor will work under their supervisor and will obey all the instructions given by supervisors.
- 12.2 All contractor must appoint their supervisor to look after the day to day activity of their labour at site.
- 12.3 Any injury/accident occurred at work place shall immediately be reported to the safety department of SPM/respective section .
- 12.4 The charges of such medical treatment will be borne by the contractor is addition to the various provisions under the ESI Act.
- 12.5 Safety helmet, belt and other safety appliances as per the requirement at the working places shall have to be provided by the contractor.
- 12.6 The firm shall have to ensure the safety of their employee during the course of employment.

NOTE: "BIDDER TO FURNISH STIPULATED DOCUMENTS ALONG WITH TENDER IN SUPPORT OF FULFILLMENT OF TENDER CRITERIA. FURTHER CORRESPONDENCE IN THIS REGARD WILL NOT BE ENTERTAINED FOR ANY REASON. NON-SUBMISSION OR INCOMPLETE SUBMISSION OF DOCUMENTS MAY LEAD TO REJECTION OF OFFER."

SIGNATURE OF BIDDER WITH NAME, DESIGNATION & SEAL



Section VII: Technical Specifications

SCOPE OF WORK, SPECIFICATIONS AND BILL OF QUANTITIES

The following provisions have been kept in renovation work of visitor room

- 1. Pile foundation for additional toilet.
- 2. Providing and fixing antiskid ceramic floor tiles in toilet floor.
- 3. Providing and fixing ceramic wall tiles in toilet wall
- 4. Providing and fixing false ceiling in visitor room.
- 5. Aluminum work for fixed door in pass section.
- 6. Construction of sewer chamber
- 7. T&P: Shall be arranged by contractor.
- 8. Time:- 05 (Five) months from issuing NAC/Purchase Order
- 9. Quantity of work: SPM authority reserve the full rights to increase or decrease the quantities of item, at the time of award tender and any time during execution of contract period or extended period of contract as per its actual requirement. SPM reserve the rights "that it is not necessary that all the items will be executed in the said period of contract and therefore the contractor has no right to claim for any works/item of works for the execution in the time period of contract or extended period of the contract."
- 10. The Firm shall maintain complete official records like material brought at site register, cement register, site order book, test register, hindrance register etc.. SPM have rights to see these records time to time and firm shall submit all records as mentioned in this point to SPM after completion of the work.
- 11. Specification: The work shall be carried out as per CPWD specification 2019 Vol.-I & II with up to date correction slips.

BILL OF QUANTITIES FOR ITEM NUMBER 10

1. Earth work in excavation by mechanical means (Hydraulic excavator) /manual means in foundation trenches or drains (not exceeding 1.5 m in width or 10 sqm on plan), including dressing of sides and ramming of bottoms, lift upto 1.5 m, including getting out the excavated soil and disposal of surplus excavated soil as directed, within a lead of 50 m. All kinds of soil

QTY:- 12.00 Cum

2. Excavating trenches of required width for pipes, cables, etc including excavation for sockets, and dressing of sides, ramming of bottoms, depth upto 1.5 m, including getting out the excavated soil, and then returning the soil as required, in layers not exceeding 20 cm in depth, including consolidating each deposited layer by ramming, watering, etc. and disposing of surplus excavated soil as directed, within a lead of 50 m –

All kinds of soil QTY:- 15 Mtr

3. Filling available excavated earth (excluding rock) in trenches, plinth, sides of foundations etc. in layers not exceeding 20cm in depth, consolidating each deposited layer by ramming and watering, lead up to 50 m and lift upto 1.5 m.

Qty:- 8 Cum

- 4. Supplying and filling stone dust in trenches, plinth, sides of foundations etc. in layers not exceeding 20cm in depth, consolidating each deposited layer by ramming and watering, for all lead and lift all complete. (The measurement shall be for compacted quantity only)

 Qty:- 2 Cum
- 5. Providing and laying in position cement concrete of specified grade excluding the cost of



centering and shuttering - All work up to plinth level :

1:4:8 (1 Cement : 4 coarse sand (zone-III) derived from natural sources : 8 graded stone aggregate 40 mm nominal size derived from natural sources)

Qty:- 3 Cum

6. Providing and laying in position specified grade of reinforced cement concrete, excluding the cost of centering, shuttering, finishing and reinforcement - All work up to plinth level :

1:1.5:3 (1 cement : 1.5 coarse sand (zone-III) derived from natural sources : 3 graded stone aggregate 20 mm nominal size de rived from natural sources)

Qty:- 5 Cum

7. Reinforced cement concrete work in walls (any thickness), including attached pilasters, buttresses, plinth and string courses, fillets, columns, pillars, piers, abutments, posts and struts etc. above plinth level up to floor five level, excluding cost of centering, shuttering, finishing and reinforcement:

1:1.5:3 (1 cement : 1.5 coarse sand(zone-III) derived from natural sources : 3 graded stone aggregate 20 mm nominal size derived from natural sources)

Qty:- 1 Cum

8. Reinforced cement concrete work in beams, suspended floors, roofs having slope up to 15° landings, balconies, shelves, chajjas, lintels, bands, plain window sills, staircases and spiral stair cases above plinth level up to floor five level, excluding the cost of centering, shuttering, finishing and reinforcement with 1:1.5:3 (1 cement : 1.5 coarse sand(zone-III) derived from natural sources : 3 graded stone aggregate 20 mm nominal size derived from natural sources). Qty:- 1.5 Cum

9. Centering and shuttering including strutting, propping etc. and removal of form for

A. Foundations, footings, bases of columns, etc. for mass concrete

Qty:- 16 Sqm

B. Suspended floors, roofs, landings, balconies and access platform

Qty:- 17 Sqm

C. Lintels, beams, plinth beams, girders, bressumers and cantilevers

Qty:- 28 Sqm

D. Columns, Pillars, Piers, Abutments, Posts and Struts

Qty:- 16 Sqm

10. Steel reinforcement for R.C.C. work including straightening, cutting, bending, placing in position and binding all complete upto plinth level

Thermo-Mechanically Treated bars of grade Fe-500D or more.

Qtv:-950 KG

11. Steel reinforcement for R.C.C. work including straightening, cutting, bending, placing in position and binding all complete above plinth level

Thermo-Mechanically Treated bars of grade Fe-500D or more.

Qty:- 600 KG

12. Brick work with modular fly ash bricks conforming to IS:12894, class designation 50 average compressive strength in super structure above plinth level up to floor V level in Cement mortar 1:6 (1 Cement: 6 coarse sand)

Qty:- 7 Cum

13. Half Brick work with modular fly ash bricks conforming to IS:12894, class designation 50 average compressive strength in super structure above plinth level up to floor V level in : Cement mortar 1:4 (1 Cement: 4 coarse sand)



Qty:-10.50 Sqm

- 14. Providing and fixing ISI marked flush door shutters conforming to IS: 2202 (Part I) decorative type, core of block board construction with frame of 1st class hard wood and well matched teak 3 ply veneering with vertical grains or cross bands and face veneers on both faces of shutters 30 mm thick including ISI marked Stainless Steel butt hinges with necessary screws Qty:-3.5 Sqm
- 15. Providing and fixing M.S. grills of required pattern in frames of windows etc. with M.S. flats, square or round bars etc. including priming coat with approved steel primer all complete Fixed to openings /wooden frames with rawl plugs screws etc.

 Qty:- 50 KG
- 16. Providing and fixing aluminium sliding door bolts, ISI marked anodised (anodic coating not less than grade AC 10 as per IS: 1868), transparent or dyed to required colour or shade, with nuts and screws etc. complete:

250x16 mm Qty:- 2 EA

17. Providing and fixing aluminium tower bolts, ISI marked, anodised (anodic coating not less than grade AC 10 as per IS: 1868) transparent or dyed to required colour or shade, with necessary screws etc. complete

200X10 mm Qty:- 4.0 EA

18. Providing and fixing aluminium handles, ISI marked, anodised (anodic coating not less than grade AC 10 as per IS: 1868) transparent or dyed to required colour or shade, with necessary screws etc. complete:

125mm Qty:-4 EA

- 19. Providing and fixing aluminium hanging floor door stopper, ISI marked, anodised (anodic coating not less than grade AC 10 as per IS: 1868) transparent or dyed to required colour and shade, with necessary screws etc. complete Qty:- 2EA
- 20. Providing and fixing pressed steel door frames conforming to IS: 4351, manufactured from commercial mild steel sheet of 1.60 mm thickness, including hinges, jamb, lock jamb, bead and if required angle threshold of mild steel angle of section 50x25 mm, or base ties of 1.60 mm, pressed mild steel welded or rigidly fixed together by mechanical means, including M.S. pressed butt hinges 2.5 mm thick with mortar guards, lock strike-plate and shock absorbers as specified and applying a coat of approved steel primer after pre-treatment of the surface as directed by Engineer-in-charge: Profile C

Fixing with adjustable lugs with split end tail to each jamb Qty: 18 Mtr

21. Providing and laying rectified Glazed Ceramic floor tiles of size 300x300 mm or more (thickness to be specified by the manufacturer), of 1st quality conforming to IS: 15622, of approved make, in colours White, Ivory, Grey, Fume Red Brown, laid on 20 mm thick cement mortar 1:4 (1 Cement: 4 Coarse sand), jointing with grey cement slurry @ 3.3 kg/ sqm including grouting the joints with white cement and matching pigments etc., complete.

Qty:- 10 Sqm

22. Providing and fixing 1st quality ceramic glazed wall tiles conforming to IS: 15622 (thickness to be



specified by the manufacturer), of approved make, in all colours, shades except burgundy, bottle green, black of any size as approved by Engineer-in-Charge, in skirting, risers of steps and dados, over 12 mm thick bed of cement mortar 1:3 (1 cement : 3 coarse sand) and jointing with grey cement slurry @ 3.3kg per sqm, including pointing in white cement mixed with pigment of matching shade complete.

Qty:- 22 Sqm

23. Providing and fixing on wall face unplasticised Rigid PVC rain water pipes conforming to IS: 13592 Type A, including jointing with seal ring conforming to IS: 5382, leaving 10 mm gap for thermal expansion,

(i) Single socketed pipes.

110 mm diameter

Qty:- 7 Mtr

24. Providing and fixing on wall face unplasticised - PVC moulded fittings/ accessories for unplasticised Rigid PVC rain water pipes conforming to IS: 13592 Type A, including jointing with seal ring conforming to IS: 5382, leaving 10 mm gap for thermal expansion

A. Bend 87.5 degree

110 mm bend

Qty:- 2 EA

B. Shoe (Plain)

110 mm Shoe

Qty;- 2 EA

25. Providing and fixing unplasticised -PVC pipe clips of approved design to unplasticised - PVC rain water pipes by means of 50x50x50 mm hard wood plugs, screwed with M.S. screws of required length, including cutting brick work and fixing in cement mortar 1:4 (1 cement : 4 coarse sand) and making good the wall etc. complete

Qty:- 6 EA

26. 12 mm cement plaster of mix:

1:6 (1 cement: 6 fine sand)

Qty;- 50 Sqm

27. 15 mm cement plaster on the rough side of single or half brick wall of mix

1:6 (1 cement: 6 fine sand)

Qty:-60 Sqm

28. 6 mm cement plaster of mix:

1:3 (1 cement : 3 fine sand)

Qty:- 20 Sqm

29. Distempering with 1st quality acrylic distemper (ready mixed) having VOC content less than 50gms/liter, of approved manufacturer, of required shade and colour complete, as per manufacturer's specification.

Two or more coats on new work

Qty:- 70 Sqm

30. Finishing walls with Premium Acrylic Smooth exterior paint with Silicone additives of required shade:

New work (Two or more coats applied @ 1.43 ltr/10 sqm over and including priming coat of exterior primer applied @ 2.20 kg/10 sqm).

Qty:-60 Sqm



31. Demolishing stone rubble masonry manually/ by mechanical means including stacking of serviceable material and disposal of unserviceable material within 50 metres lead as per direction of Engineer-in-charge

Qty:- 2 Cum

32. Providing and fixing white vitreous china pedestal type water closet (European type W.C. pan) with seat and lid, 10 litre low level white P.V.C. flushing cistern, including flush pipe, with manually controlled device (handle lever), conforming to IS: 7231, with all fittings and fixtures complete, including cutting and making good the walls and floors wherever required:

W.C. pan with ISI marked white solid plastic seat and lid

Qty:-1EA

33. Providing and fixing water closet squatting pan (Indian type W.C. pan) with 100 mm sand cast Iron P or S trap, 10 litre low level white P.V.C. flushing cistern, including flush pipe, with manually controlled device (handle lever) conforming to IS: 7231, with all fittings and fixtures complete, including cutting and making good the walls and floors wherever required

White Vitreous china Orissa pattern W.C. pan of size 580x440 mm with integral type foot rests Qty:- 1 EA

34. Providing and fixing one piece construction white vitreous china squatting plate with an integral longitudinal flushing pipe, white P.V.C. automatic flushing cistern, with fittings, standard size G.I. / PVC flush pipe for back and front flush with standard spreader pipes with fittings, G.I clamps and C.P. brass coupling complete, including painting of fittings and cutting and making good the walls and floors etc. wherever required:

Range of two squatting plates with 5 litre P.V.C. automatic flushing cistern Qty:- 1 EA

35. Providing and fixing wash basin with C.I. brackets, 15 mm C.P. brass pillar taps, 32 mm C.P. brass waste of standard pattern, including painting of fittings and brackets, cutting and making good the walls wherever require:

White Vitreous China Washbasin size of 630x450mm with a single 15 mm C.P. brass pillar tap Qty:- 2 EA

36. Providing and fixing 600x450 mm beveled edge mirror of superior glass (of approved quality) complete with 6 mm thick hard board ground fixed to wooden cleats with C.P. brass screws and washers complete

Qty:- 1 EA

37. Providing and fixing mirror of superior glass (of approved quality) and of required shape and size with plastic moulded frame of approved make and shade with 6 mm thick hard board backing Rectangular shape 1500x450 mm

Qty:- 2 EA

38. Providing and fixing soil, waste and vent pipes

100 mm dia

Hubless centrifugally cast (spun) iron pipes epoxy coated inside & outside IS:15905 Qty:-10 Mtr

39. Providing and fixing plain bend of required degree

100 mm dia

Hubless centrifugally cast (spun) iron pipes epoxy coated inside & outside IS:15905 Qty:-3 EA

40. Providing and fixing terminal guard:

100 mm dia



Hubless centrifugally cast (spun) iron pipes epoxy coated inside & outside IS:15905 Qty:-1 EA

41. Providing and fixing shielded coupling for Hubless centrifugally cast iron pipe 100 mm dia

Hubless centrifugally cast (spun) iron pipes epoxy coated inside & outside IS:15905 Qty:-10 EA

42. Providing and fixing trap of self cleansing design with screwed down or hinged grating with or without vent arm complete, including cost of cutting and making good the walls and floors:

100 mm inlet and 100 mm outlet

Hubless centrifugally cast (spun) iron epoxy coated inside & outside as per IS:15905 Qty:-02 EA

43. Providing and fixing Chlorinated Polyvinyl Chloride (CPVC) pipes, having thermal stability for hot & cold water supply, including all CPVC plain & brass threaded fittings, i/c fixing the pipe with clamps at 1.00 m spacing. This includes jointing of pipes & fittings with one step CPVC solvent cement and the cost of cutting chases and making good the same including testing of joints complete as per direction of Engineer in Charge. Concealed work, including cutting chases and making good the walls etc.

15 mm nominal dia Pipes

Qty;- 1 Mtr

44. Providing and fixing Chlorinated Polyvinyl Chloride (CPVC) pipes, having thermal stability for hot & cold water supply including all CPVC plain & brass threaded fittings This includes jointing of pipes & fittings with one step CPVC solvent cement, trenching, refilling & testing of joints omplete as per direction of Engineer in Charge. External work 20 mm nominal dia Pipes

Ot ... 45 Mt.

Qty:- 15 Mtr

- 45. Providing and placing on terrace (at all floor levels) polyethylene water storage tank, IS: 12701 marked, with cover and suitable locking arrangement and making necessary holes for inlet, outlet and overflow pipes but without fittings and the base support for tank. Qty:- 1000 Ltr
- 46. Providing and fixing C.P. brass bib cock of approved quality conforming to IS:8931 : 15 mm nominal bore Qty :- 4 EA
- 47. Providing and fixing C.P. brass angle valve for basin mixer and geyser points of approved quality conforming to IS:8931 15 mm nominal bore Qty:- 2 EA
- 48. Providing and fixing C.P. Brass extension nipple (size 15mmx50mm) of approved make and quality as per direction of Engineer-in-charge Qty:- 4 EA
- 49. Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/appropriate Z sections and other sections of approved makeconforming to IS: 733 and IS: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/ neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing / paneling, C.P. brass / stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge. (Glazing, paneling and dash



fasteners to be paid for separately):

A. For fixed portion Polyester powder coated aluminium (minimum thickness of polyester powder coating 50 micron)

Qty:-60 KG B. For shutters of doors, windows & ventilators including providing and fixing hinges/pivots and making provision for fixing of fittings wherever required including the cost of EPDM rubber / neoprene gasket

required (Fittings shall be paid for separately) Polyester powder coated aluminium (minimum thickness of polyester powder

coating 50 micron)

Qty:-20 KG

50. Providing and fixing glazing in aluminium door, window, ventilator shutters and partitions etc. with EPDM rubber / neoprene gasket etc. complete as per the architectural drawings and the directions of engineer-in-charge. (Cost of aluminium snap beading shall be paid in basic item): A. With float glass panes of 4.0 mm thickness (weight not less than 10kg/sqm)

Qty:- 4 Sqm B. With float glass panes of 8 mm thickness (weight not less than 20 kg/sqm)

Qty:- 10 Sqm

51. Providing and fixing factory made single extruded WPC (Wood Polymer Composite) solid door/window/ Ceosetory windows & other Frames/Chowkhat comprising of virgin PVC polymer of K value 58-60 (Suspension Grade), calcium carbonate and natural fibers (wood powder/ rice husk/wheat husk) and non toxic additives (maximum toxicity index of 12 for 100 gms) fabricated with miter joints after applying PVC solvent cement and screwed with full body threaded star headed SS screws having minimum frame density of 750 kg/ cum, screw withdrawal strength of 2200 N (Face) & 1100 N (Edge), minimum compressive strength of 58 N/mm2, modulus of elasticity 900 N/mm2 and resistance to spread of flame of Class A category with property of being termite/borer proof, water/moisture proof and fire retardant and fixed in position with M.S hold fast/lugs/SS dash fasteners of required dia and length complete as per direction of Engineer-In- Charge. (M.S hold fast/lugs or SS dash fasteners shall be paid for separately). Note: For WPC solid door/window frames, minus 5mm tolerance in dimensions i.e depth and width of profile shall be acceptable. Variation in profile dimensions on plus side shall be acceptable but no extra payment on this account shall

be made.

Frame size 65 x 100 mm

Qty:- 10 Mtr

52. Providing and fixing factory made single extruded WPC (Wood Polymer Composite) solid plain flush door shutter of required size comprising of virgin polymer of K value 58-60 (Suspension Grade), calcium carbonate and natural fibers (wood powder/ rice husk/wheat husk) and non toxic additives (maximum toxicity index of 12 for 100 gms) having minimum density of 650 kg/cum and screw withdrawal strength of 1800 N (Face) & 900 N (Edge), minimum compressive strength 50 N/mm2, modulus of elasticity 850 N/mm2 and resistance to spread of flame of Class A category with property of being termite/borer proof, water/moisture proof and fire retardant and fixing with stainless steel butt hinges of required size with necessary full body threaded star headed counter sunk S.S screws, all as per direction of Engineer-In- Charge. (Note: stainless steel butt hinges and necessary S.S screws shall be paid

separately)

35 mm thick

Qty:- 5 Sqm

53. Providing and fixing Swan Neck CP Brass pillar tap (IS 8931) of approved quality for ovel wash basin

Qtv:- 3 EA

54. Providing and fixing Stainless Steel grating of approved quality and colour

Circular type-125mm nominal dia with 25mm waste hole



Qty:-3 EA

55. Boring providing and installing cast in situ single under reamed piles of specified diameter and length below pile cap in cement concrete 1:1.5:3 (1 cement : 1.5 coarse sand : 3 stone aggregate 20mm nominal size), to carry a safe working load not less than specified, excluding the cost of steel reinforcement but including the cost of boring with augar and the length of the pile to be embedded in pile cap etc. all complete. (Length of pile for payment shall be measured upto to the bottom of pile cap) :

300 mm dia pile

Qty:- 30 Mtr

56. Water proofing treatment in horizontal and vertical surface with water based polyurethane coating (PU) with ecofrendly properties. Preparation of the surface by using suitable means like grinding, treating the cracks by making V grooves and filling the groove by bituminouse compound of approved makes, providing and applying primer coat of water based PU after diluting with 50% of water @ 0.30 Kg/Sqm or as per manufacturers specifications, providing and applying first coat of PU coating material @ 0.80 Kg/Sqm or as per manufacturers specification by brush/roller then providing and applying second coat of PU coating material @ 0.70-.080 kg/SPM or as per manufacturers specification, suitable interval between first and second coat should be kept as per manufacturers specification. Final layer developed after final coat should not be less than 1.5mm. the operation shall be carried out after scraping and properly cleaning the surface to remove loose particles with brushes complete in all respect as per direction of EIC. (The product performance shall carry guarantee for ten years against any leakage has to be insured by contractor 10% of amount will be

withheld against this item)

Qty:-12 Sqm

57. Providing and laying non-pressure NP2 class (light duty) R.C.C. pipes with collars jointed with stiff mixture of cement mortar in the proportion of 1:2 (1 cement : 2 fine sand) including testing of joints etc. complete 150 mm dia. R.C.C. pipe

Qty:- 15 Mtr

58. Constructing brick masonry manhole in cement mortar 1:4 (1cement: 4 coarse sand) with R.C.C. top slab with 1:1.5:3 mix (1 cement: 1.5 coarse sand (zone-III): 3 graded stone aggregate 20 mm nominal size), foundation concrete 1:4:8 mix (1 cement: 4 coarse sand (zone-III): 8 graded stone aggregate 40 mm nominal size), inside plastering 12 mm thick with cement mortar 1:3 (1 cement: 3 coarse sand) finished with floating coat of neat cement and making channels in cement concrete 1:2:4 (1 cement: 2 coarse sand: 4 graded stone aggregate 20 mm nominal size) finished with a floating coat of neat cement complete as per

standard design: Inside size 90x80 cm and 60 cm deep including C.I. cover with frame (light duty) 455x610 mm internal dimensions, total weight of cover and frame to be not less than 38 kg (weight of cover 23 kg and weight of

frame 15 kg): With common burnt clay F.P.S. (non modular) bricks of class designation 7.5 Qty:- 1 EA

59. Providing and fixing G.I. pipes complete with G.I. fittings and

clamps, i/c cutting and making good the walls etc.

Exposed on wall-20 mm dia nominal bore

Qty:- 15 Mtr

60. Removing white or colour wash by scrapping and sand papering and preparing the surface smooth including necessary repairs to scratches

etc. complete

Qty:- 100 Sqm

61. Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall

surface to prepare the surface even and smooth complete.

Qtv: 100 Sam

62. Finishing walls with Premium plastic acrylic emulsion of interior

grade, having VOC content less than 50 grams/ litre. New work (Two or more coats applied @ 1.43



ltr/10 sqm over and including priming coat of exterior primer applied @ 2.20 kg/10 sqm) Qty:-100 Sqm

BILL OF QUANTITIES FOR ITEM NUMBER 20 1. Providing and Fixing 15 mm thick densified tegular edged eco friendly light weight calcium silicate false ceiling tiles of approved texture of size 595 x 595 mm in true horizontal level, suspended on inter locking metal grid of hot dipped galvanised steel sections (galvanising @ 120 grams per sqm including both side) consisting of main 'T' runner suitably spaced at joints to get required length and of size 24x38 mm made from 0.33 mm thick (minimum) sheet, spaced 1200 mm centre to centre, and cross "T" of size 24x28 mm made out of 0.33 mm (Minimum) sheet, 1200 mm long spaced between main'T' at 600 mm centre to centre to form a grid of 1200x600 mm and secondary cross 'T' of length 600 mm and size 24 x28 mm made of 0.33 mm thick Minimum) sheet to be inter locked at middle of the 1200x 600 mm panel to from grid of size 600x600 mm, resting on periphery walls /partitions on a Perimeter wall angle pre-coated steel of size(24x24X3000 mm made of 0.40 mm thick (minimum) sheet with the help of rawl plugs at 450 mm centre to centre with 25 mm long dry wall screws @ 230 mm interval and laying 15 mm thick densified edges calicum silicate ceiling tiles of approved texture in the grid, including, cutting/ making opening for services like diffusers, grills, light fittings, fixtures, smoke detectors etc., wherever required. Main 'T' runners to be suspended from ceiling using G.I. slotted cleats of size 25x35x1.6 mm fixed to ceiling with 12.5 mm dia and 50 mm long dash fasteners. 4 mm G.I. adjustable rods with galvanised steel level clips of size 85 x 30 x 0.8 mm, spaced at 1200 mm centre to centre along main 'T', bottom exposed with 24 mm of all Tsections shall be pre-painted with polyster baked paint, for all heights, as per specifications, drawings and as directed by

Engineer-in-Charge. Only calcium silicate false ceiling area will be measured from wall to wall. No deduction shall be made for exposed frames/opening (cut outs) having area less than 0.30 sqm.The calcium silicate ceiling tile shall have NRC value of 0.50 (Minimum), light reflection > 85%, non-combustible as per B.S. 476 part IV, 100% humidity resistance and also having thermal conductivity <0.043 w/mK.

Qty:-33 Sqm



Section VIII: Quality Control Requirements

Execution of work and material involved in this work shall have to comply as per CPWD-DSR.



Section IX: Qualification/ Eligibility Criteria

Experience & Past Performance:

The bidder should have experience of having successfully completed similar works during last 7 years ending on 31.03.2022.

- a. Three similar completed works each costing not less than the amount equal to Rs. 3,47,936/-
- b. Two similar completed works each costing not less than the amount equal to Rs.4,34,920/-.
- c. One similar completed work costing not less than the amount equal to Rs.6,95,873/-

Capability - Equipment & manufacturing Facilities:

The bidder should be enlisted in either Central Public Works Department (CPWD) or Military Engineering Services (MES) or any other Government / PSU / Autonomous bodies.

Financial Standing:

The average annual financial turnover of the bidder during the last three years, ending on 31.03.2022, should be at least Rs.3,47,936/- (or equivalent in foreign currency at exchange rate prevalent on '31.03.2022 as per the annual report (audited balance sheet and profit & loss account) of the relevant period, duly authenticated by a Chartered Accountant/ Cost Accountant in India or equivalent in relevant countries.

The bidder should not have suffered any financial loss for more than one year during the last three years, ending on 31.03.2022.

i) The net worth of the Bidder should not be negative on 31.03.2022 and also ii) should not have eroded by more than 30% in the last three years, ending on 31.03.2022.

NOTE:

- All experience, past performance and capacity/capability related data should be certified by the Authorized Signatory of the Bidder firm. The credentials regarding experience and past performance to the extent required as per the above eligibility criteria as submitted by the bidder may be verified by the parties for whom work has been done.
- **2.** All financial standing data should be certified by Chartered Accountants (CA) in India and certified Public Accountant/ Chartered Accountants of other countries.
- 3. MSME firms shall be exempted from financial standing and past experience excluding Net worth criteria.
- 4. Bidder shall submit the supporting document in support of above.



Date.....

Section X: Tender Form

To,
(Complete address of SPMCIL)
Ref: Your Tender document No: 6000017712/Civil/700, Dated: 24.08.2022
Marches and and march the company of the selection of the desired

If our tender is accepted, we undertake to supply the goods and perform the services as mentioned above, in accordance with the delivery schedule specified in the List of Requirements.

We further confirm that, if our tender is accepted, we shall provide you with a performance security of required amount in an acceptable form in terms of GCC clause 6, read with modification, if any, in Section V – "Special Conditions of Contract", for due performance of the contract.

We agree to keep our tender valid for acceptance for a period upto......, as required in the GIT clause19, read with modification, if any in Section-III - "Special Instructions to Tenderers" or for subsequently extended period, if any, agreed to by us. We also accordingly confirm to abide by this tender upto the aforesaid period and this tender may be accepted any time before the expiry of the aforesaid period. We further confirm that, until a formal contract is executed, this tender read with your written acceptance thereof within the aforesaid period shall constitute a binding contract between us.

We confirm that in case of downloaded Tender Document, we have not changed/ edited its contents. We realise that in case any such change is noticed at any stage including after the award of contract, we would be liable to action under clause 44 of the GIT.

We further understand that you are not bound to accept the lowest or any tender you may receive against your above-referred tender enquiry.

We also solemnly declare as under:



1. MSMEs Status:

Having read and understood the Public Procurement Policy for Micro and Small Enterprises (MS	SEs)
Order, 2012 (as amended and revised till date), and solemnly declare the following:	

Olu	or, 2012 (as amended and revised till date), and soleminy declare the following.
(a)	Company/Partnership Firm/Proprietary Concern/Society/Trust /NGO/Others (Please Specify):
(b)	Micro/ Small / Medium Enterprise/ SSI/ Govt. Dep't. / PSU/ Others:
(c)	Name of MSME Registering Body (NSIC/ DIC/ KVIC/KVIB etc.):
(d)	MSME Registration no. (with copy of registration):
(e)	Udyog Aadhar Memorandum no
(f)	Whether Proprietor/ Partner belongs to SC/ ST or Women category (Please specify names and percentage of shares held by SC/ST Partners):
2. [Make in India Status:
201	ring read and understood the Public Procurement (Preference to Make in India PPP_MII) Order, 7 (as amended and revised till date) and related notifications from the relevant Nodal Ministry/partment, and solemnly declare the following:
(a) (b)	☐ There is no country whose bidders have been notified as ineligible on reciprocal basis
	under this order for offered product, or We do not belong to any Country whose bidders are notified as ineligible on reciprocal basis under this order
	Restrictions on procurement from bidders from a country or countries, or a class of countries under Rule 144 (xi) of the General Financial Rules 2017
F	Having read and understood the Order (Public Procurement No. 1) issued vide F.No.6/18/2019-PPD dated 23 rd July 2020 (and its amendments if any) by Department of Expenditure, Ministry of Finance under the above provision and solemnly declare the following:
	□ We do not belong to any Country whose bidders are notified as ineligible under this order
	Debarment Status: Please state whether business dealings with you currently stand suspended/panned by any Ministry/ Depts. of Government of India or by any State Govt:
	 Yes (with period of Ban) No, We, solemnly declare that neither we nor any of our affiliates or subsidiaries – including



subcontractors or suppliers for any part of the contract—do not stand declared ineligible/blacklisted/banned/debarred by any Government Agency anywhere in the world, for participating in its tenders, under that country's laws or official regulations.

5.	Penalties for false or misleading declarations: I/we hereby confirm that the particulars given
	above are correct and complete and also undertake to advise any future changes to the above
	details. We understood that any wrong or misleading self-declaration by us would be violation of
	code of Ethics and would attract penalties as mentioned in this tender document, including
	debarment.
	(Signature with date)
	(Oignature with date)
	Name and declaration
	Name and designation
	Duly authorized to sign tender for and on behalf of



Section XI: Price Schedule

(As per Annexure-I)

OFFER FORM for Tender No
We
Price Schedule as per Annexure-1 1. Scope of Work: Construction of Ladies Toilet Along With False Ceiling on Visitor Room. as per Section-VII.
 2. Taxation Details: a. PAN number b. Type of GST Registration (Registered, Unregistered, Composition, SEZ, RCM etc.) c. GSTIN number d. Registered Address as per GST registration and Place of Delivery for GST Purpose e. Contact Names, Nos. & email IDs for GST matters (Please mention primary and secondary contacts)
3. It is hereby certified that we have understood the General and Special Instructions to Tenderers (GIT and SIT), and also the General and Special Conditions of Contract (GCC and SCC) attached to the tender and have thoroughly examined specifications/ Quality Control Requirements and other stipulations in Section VII & VIII – Technical Specifications and Quality Control Requirements; and are thoroughly aware of the nature of stores required and our offer is to supply stores strictly in accordance with the requirements and according to the terms of the tender. We agree to abide solely by the General and Special Conditions of Contract and other conditions of the tender in accordance with the tender documents if the contract is awarded to us
4. We hereby offer to supply the stores detailed above or such portion thereof, as you may specify in the acceptance of tender at the price quoted and agree to hold this offer open for acceptance for a period ofdays from the date of opening of tender (i.e., upto), We shall be bound by the communication of acceptance despatched.
5. Earnests Money/Bid Guarantee for an amount equal to is enclosed in form of (form and reference number, date) as per the Tender Documents.
6. The method of evaluation of L1 criteria for awarding the contract shall be decided taking into consideration the total landed price up to SPM Narmadapuram.
7. TCS (u/s 206C (1 H) of IT Act is not applicable, as SPM will deduct TDS u/s 194Q.
Dated Signature and seal of Manufacturer/Bidder
Note:

The Bidder may prepare their own offer forms as per this proforma.



- (ii) No change in the proforma is permissible.
- (iii) No erasures or alternations in the text of the offer are permitted. Any correction made in the offer shall be initialled by the bidder.
- (iv) Figures in Columns 5 to 7 (both inclusive) and in Break-up of price in column 6, should be in both figures and words.
- (v) This Section should not bring in any new Technical Parameter that has not been mentioned in the Technical Bid.



1. Vendor/ Contractor particulars:

Section XII Vendor Details

The tenderer should furnish specific details mentioned below. In case a question/issue does not apply to a tenderer, the same should be answered with the remark "not applicable".

Wherever necessary and applicable, the tenderer shall enclose certified copy as documentary proof/ evidence to substantiate the corresponding statement.

In case a tenderer furnishes a wrong or misleadin g answer against any of the under mentioned question/ issues, its tender will be liable to be ignored.

	(a)	Name of the Company:
	(b)	Corporate Identity No. (CIN):
	(c)	Registration if any with SPMCIL:
	(d)	Complete Postal Address:
	(e)	Pin code/ ZIP code:
	(f)	Telephone nos. (with country/area codes):
	(g)	Fax No.: (with country/area codes):
	(h)	Cell phone Nos.: (with country/area codes):
	(i)	Contact persons /Designation:
	(j)	Email IDs:
2.	Taxa	tion Details:
	(a)	PAN Number:
	` ,	Type of GST Registration (Registered, Unregistered, Composition, SEZ, RCM etc.):
	, ,	GSTIN number:
		Registered Address as per GST registration and Place of Delivery for GST Purpose:
	(u)	registered Address as per Got registration and riace of Delivery for Got Fulpose.
	` '	Contact Names, Nos. & email IDs for GST matters (Please mention primary and secondary contacts):



	We solemnly declare that our GST rating on the GST portal / Govt. official website is NOT negative / blacklisted during the last three financial years.
(Signature w	vith date)
(Full name,	designation & address of the person duly authorized sign on behalf of the tenderer) behalf of
(Name, add	ress, and stamp of the tendering firm)



Section XIV: Manufacturer's Authorization Form

To
(Name and address of SPMCIL)
Dear Sirs,
Ref. Your Tender document No, dated
We,
(name and address of the above agent) is authorized to submit a tender, process the same further and enter into a contract with you against your requirement as contained in the above referred tender enquiry documents for the above goods manufactured by us.
We also hereby extend our full warranty, as applicable as per clause 16 of the General Conditions of Contract read with modification, if any, in the Special Conditions of Contract for the goods and services offered for supply by the above firm against this tender document.
Yours faithfully,
[Signature with date, name, and designation]
for and on behalf of Messrs
Name & address of the manufacturers

Note: This letter of authorization should be on the letter head of the manufacturing firm and should be signed by a person competent and having the power of attorney to legally bind the manufacturer.



Section XV: Bank Guarantee Form for Performance Security

PROFORMA OF BANK GUARANTEE FOR CONTRACT PERFORMANCE GUARANTEE BOND

(C	ON BANK'S LETTERHEAD WITH ADHESIVE STAMP)
Re	ef Date
Ва	ank Guarantee No
To	О,
(II	nsert Name & Address of the Purchaser)
De	ear Sir,
1.	Against contract vide Notification for Award of the Tender No
2.	We
3.	It is fully understood that this guarantee is effective from the date of the said contract and that we (name of the bank), undertake not to revoke this guarantee during its currency, without the consent in writing of the Purchaser.



4.	We undertake to pay to the Purchaser, any money so demanded, notwithstanding any dispute or
	disputes raised by the Contractor, in any suit or proceeding pending before any Court or Tribunal,
	relating thereto, our liability under this present, being absolute and unequivocal. The payments so
	made by us under this bond, shall be a valid discharge of our liability for payment thereunder, and
	the Contractor shall have no claim against us, for making such payments.

	the Contractor shall have no claim against us, for making such payments.
5.	We
	(name of the bank), shall not be released from our liability under
	of the bank), shall not be released from our liability under this guarantee, by reason of any such variation or extension being granted to the said Contractor, or for any forbearance and/or omission on the part of the Purchaser, or any indulgence by the Purchaser towards the said Contractor, or by any other matter or thing whatsoever, which under the law relating to sureties, would, but for this provision, have the effect of so releasing us from our liability under this guarantee.
6.	This guarantee will not be discharged due to the change in the constitution of the Bank or the Contractor.
Da	ite:
Pla	ace:
Się	gnature
(P	rinted Name)
(D	esignation)
Wi	tnesses

(Bank's Common Seal)



Section XVI: Contract Form

(Ac	Idress of SPMCIL's office issuing the contract)
Coı	ntract No dated
Thi	s is in continuation to this office' Notification of Award No dated
1.	Name & address of the Supplier
2.	SPMCIL's Tender document No
3.	Supplier's Tender No

- 4. In addition to this Contract Form, the following documents etc, which are included in the documents mentioned under paragraphs 2 and 3 above, shall also be deemed to form and be read and construed as part of this contract:
 - (i) General Conditions of Contract;
 - (ii) Special Conditions of Contract;
 - (iii) List of Requirements;
 - (iv) Technical Specifications;
 - (v) Quality Control Requirements;
 - (vi) Tender Form furnished by the supplier;
 - (vii) Price Schedule(s) furnished by the supplier in its tender;
 - (viii) Manufacturers' Authorization Form (if applicable for this tender);
 - (ix) SPMCIL's Notification of Award

Note: The words and expressions used in this contract shall have the same meanings as are respectively assigned to them in the conditions of contract referred to above. Further, the definitions and abbreviations incorporated under Section – V - 'General Conditions of Contract' of SPMCIL's Tender document shall also apply to this contract.

- 5. Some terms, conditions, stipulations etc. out of the above-referred documents are reproduced below for ready reference:
 - (i) Brief particulars of the goods and services which shall be supplied/ provided by the supplier are as under:

Schedule No.	Brief description of goods/ services	Accounting unit	Quantity to be supplied	Unit Price (in Rs.)	Total price



An	Any other additional services (if applicable) and cost there	of:
То	Total value (in figure) (In wo	rds)
(ii) (iii) (iv) (v) (vi) (vii) (viii) (ix)	iii) Details of Performance Security iv) Quality Control (a) Mode(s), stage(s), and place(s) of conducting inspection (b) Designation and address of SPMCIL's inspecting of (v) Destination and dispatch instructions vi) Consignee, including port consignee, if any vii) Warranty clause viii) Payment terms	
(Sigı	Signature, name, and address of SPMCIL's authorized office	cial)
For	For and on behalf of	
Rec	Received and accepted this contract	
. •	Signature, name, and address of the supplier's executive d supplier)	uly authorized to sign on behalf of the
For	For and on behalf of	
	Name and address of the supplier)	
	Seal of the supplier)	
Date	Date:	
Plac	Place:	



The General Manager

Section XVII: Letter of Authority for attending / Bid Opening (Refer to clause 24.2 of GIT)

Ç					
Unit Address					
Subject: Authorization for attending bid opening on (date) in the Tender of					
Following persons are hereby aut					
Order of Preference	Name	Specimen Signatures			
I.					
II.					
Alternate Representative					
Signatures of bidder or					
Officer authorized to sign the bid Documents on behalf of the bidder					

NOTE

- 1. Maximum of two representatives will be permitted to attend pre-bid conference/bid opening. In cases where it is restricted to one, first named representative will be allowed to attend. Alternate representative will be permitted when regular representatives are not able to attend.
- 2. In case of pre-bid conference, self-attested copy of proof of purchase of Bid documents, in the name of the bidder must be enclosed with this authorization, without which entry would be refused. Bid documents would be available for sale at the site also.
- 3. Permission for entry to the hall where even is held may be refused in case authorization as prescribed above is not produced.



Section XVIII: Proforma of Bills for Payments (Refer Clause 22.6 of GCC)

Name a	nd Address of the f	-irm				
Bill No .			Dated			
Purchase order			No	Dated		
Name a	nd address of the o	consignee				
S. No	Authority for purchase	Description of Stores	Number or quantity	Rate Rs. P.	Price per Rs. P.	Amour
Total						
 Free Exercise Pa Oth 	ST/ CGST/ SGST/ Usight (if applicable) cise Duty (if applicacking and Forwardiners (Please specify C Amount (with cal	ble) ng charges (if appli)	cable)			
7. (-)	deduction/Discount					
8. Ne	Net amount payable (in words Rs.)					
Dispatch	n detail RR No. othe	er proof of dispatch	·			
Dated					(encl	osed)
Inspecti	on Certificate No		dated		(encl	osed)
Place a	nd Date					
Receive	ed Rs					
Rupees)					



We solemnly certify that:

- a. Goods and Services Tax (GST) charged on this Bill is not more than what is payable under the provision of the relevant Act or the Rules made there under.
- b. Goods on which GST has been charged have not been exempted under the GST Act or the rules made there under and the charges on account of GST on these goods are correct under the provisions of that Act or the Rules made there under.
- c. We are registered with above indicated GSTIN as dealer in the State where in their Billing address is located for the purpose of GST.
- d. This bill form / invoice is not a replacement for the GST invoice. The proper GST invoice as per requirements of GST rules has been sent to the Purchaser as and when deliveries are made to the consignee.
- e. That the payment being claimed is strictly in terms of the contract and all the obligations on the part of the supplier for claiming that payment has been fulfilled as required under the contract.

Revenue stamp

Signature and of Stamp Supplier



Section XIX: NEFT Mandate (Refer clause 22.2 of GCC)

From	: IM/S	Date:			
To:					
(Inse	t Name and Address of Purchaser's Payin	g Authority as per NIT Clause 1)			
Sub:	NEFT payments				
above	efer to RBI's NEFT scheme. Our manda e scheme to our under noted account. ONAL ELECTRONIC FUNDS TRANSFER	te SPMCIL for making payments to us through the			
1.	Name of City				
2.	Bank Code No.				
3.	Branch Code No.				
4.	Bank's Name				
5.	Branch Address				
6.	Branch Telephone / Fax No.				
7.	Supplier's Account No.				
8.	Type of Account				
9.	IFSC code for NEFT				
10.	IFSC code for RTGS				
11.	Supplier's name as per Account				
12.	MICR Code No.				
phot	In Lieu of Bank Certificate to be obtained as under, please attach a bank cancelled cheque or photocopy of a cheque or front page of your bank passbook issued by your bank for verification of the above particulars.				

I hereby declare that the particulars given above are correct and complete. If the transaction is delayed or not effected at all for reasons of incomplete or incorrect information, I would not hold the user institution responsible. I have read the option intimation letter and agree to discharge responsibility expected of me as a participant under the scheme.



Date

Signature of the Customer

Certified that the above particulars are correct as per our record.

Stamp and
Signature of authorized
Official of the bank



ANNEXURE-I

Section XI: Price Schedule

TENDER NO. 6000017712/CIVIL/700 Dt. 27.08.2022

The Price bid should clearly indicate the break-up of the price as under:-

GSTIN No. of your Firm:

Sr.	Description	HSN	Qty	Unit	Rate	Amount
No. Item No.10	Earth work in excavation by mechanical means (Hydraulic excavator) /manual means in foundation trenches or drains		12	Cum		
	(not exceeding 1.5 m in width or 10 sqm on plan), including dressing of sides and ramming of bottoms, lift upto 1.5 m, including getting out the excavated soil and disposal of surplus excavated soil as directed, within a lead of 50 m. All kinds of soil					
2	Excavating trenches of required width for pipes, cables, etc including excavation for sockets, and dressing of sides, ramming of bottoms, depth upto 1.5 m, including getting out the excavated soil, and then returning the soil as required, in layers not exceeding 20 cm in depth, including consolidating each deposited layer by ramming, watering, etc. and disposing of surplus excavated soil as directed, within a lead of 50 m – All kinds of soil		15	M		
3.	Filling available excavated earth (excluding rock) in trenches, plinth, sides of foundations etc. in layers not exceeding 20cm in depth, consolidating each deposited layer by ramming and watering, lead up to 50 m and lift upto 1.5 m.		8.000	Cum		
4.	Supplying and filling stone dust in trenches, plinth, sides		2.000	Cum		



	of foundations etc. in layers not exceeding 20cm in depth, consolidating each deposited layer by ramming and watering, for all lead and lift all complete. (The measurement shall be for compacted quantity only)			
5.	Providing and laying in position cement concrete of specified grade excluding the cost of centering and shuttering - All work up to plinth level: 1:4:8 (1 Cement: 4 coarse sand (zone-III) derived from natural sources: 8 graded stone aggregate 40 mm nominal size derived from natural sources)	3.000	Cum	
6.	Providing and laying in position specified grade of reinforced cement concrete, excluding the cost of centering, shuttering, finishing and reinforcement - All work up to plinth level: 1:1.5:3 (1 cement: 1.5 coarse sand (zone-III) derived from natural sources: 3 graded stone aggregate 20 mm nominal size de rived from natural sources)	5.000	Cum	
7.	Reinforced cement concrete work in walls (any thickness), including attached pilasters, buttresses, plinth and string courses, fillets, columns, pillars, piers, abutments, posts and struts etc. above plinth level up to floor five level, excluding cost of centering, shuttering, finishing and reinforcement: 1:1.5:3 (1 cement: 1.5 coarse sand(zone-III) derived from natural sources: 3 graded stone aggregate 20 mm nominal size derived from natural sources)	1.000	Cum	



8.	Reinforced cement concrete work in beams, suspended floors, roofs having slope up to 15° landings, balconies, shelves, chajjas, lintels, bands, plain window sills, staircases and spiral stair cases above plinth level up to floor five level, excluding the cost of centering, shuttering, finishing and reinforcement with 1:1.5:3 (1 cement : 1.5 coarse sand(zone-III) derived from natural sources : 3 graded stone aggregate 20 mm nominal size derived from natural sources).	1.500	Cum	
9.	Centering and shuttering including strutting, propping etc. and removal of form for			
A	Foundations, footings, bases of columns, etc. for mass concrete	16	Sqm	
В	Suspended floors, roofs, landings, balconies and access platform	17	Sqm	
С	Lintels, beams, plinth beams, girders, bressumers and cantilevers	28	Sqm	
D	Columns, Pillars, Piers, Abutments, Posts and Struts	16	Sqm	
10	Steel reinforcement for R.C.C. work including straightening, cutting, bending, placing in position and binding all complete upto plinth level Thermo-Mechanically Treated bars of grade Fe-500D or more.	950	KG	
11	Steel reinforcement for R.C.C. work including straightening, cutting, bending, placing in position and binding all complete above plinth level	600	KG	



	Thermo-Mechanically Treated bars of grade Fe-500D or more.			
12	Brick work with modular fly ash bricks conforming to IS:12894, class designation 50 average compressive strength in super structure above plinth level up to floor V level in Cement mortar 1:6 (1 Cement: 6 coarse sand)	7	Cum	
13.	Half Brick work with modular fly ash bricks conforming to IS:12894, class designation 50 average compressive strength in super structure above plinth level up to floor V level in: Cement mortar 1:4 (1 Cement: 4 coarse sand)	10.50	Sqm	
14.	Providing and fixing ISI marked flush door shutters conforming to IS: 2202 (Part I) decorative type, core of block board construction with frame of 1st class hard wood and well matched teak 3 ply veneering with vertical grains or cross bands and face veneers on both faces of shutters 30 mm thick including ISI marked Stainless Steel butt hinges with necessary screws	3.5	sqm	
15.	Providing and fixing M.S. grills of required pattern in frames of windows etc. with M.S. flats, square or round bars etc. including priming coat with approved steel primer all complete Fixed to openings /wooden frames with rawl plugs screws etc.	50	KG	
16	Providing and fixing aluminium sliding door bolts, ISI marked anodised (anodic	2	EA	



	coating not less than grade AC 10 as per IS: 1868), transparent or dyed to required colour or shade, with nuts and screws etc. complete: 250x16 mm			
17	Providing and fixing aluminium tower bolts, ISI marked, anodised (anodic coating not less than grade AC 10 as per IS: 1868) transparent or dyed to required colour or shade, with necessary screws etc. complete 200X10 mm	4.000	EA	
18	Providing and fixing aluminium handles, ISI marked, anodised (anodic coating not less than grade AC 10 as per IS: 1868) transparent or dyed to required colour or shade, with necessary screws etc. complete: 125mm	4.000	EA	
19	Providing and fixing aluminium hanging floor door stopper, ISI marked, anodised (anodic coating not less than grade AC 10 as per IS: 1868) transparent or dyed to required colour and shade, with necessary screws etc. complete	2.000	EA	
20	Providing and fixing pressed steel door frames conforming to IS: 4351, manufactured from commercial mild steel sheet of 1.60 mm thickness, including hinges, jamb, lock jamb, bead and if required angle threshold of mild steel angle of section 50x25 mm, or base ties of 1.60 mm, pressed mild steel welded or rigidly fixed together by mechanical means, including M.S. pressed butt hinges 2.5 mm thick with mortar guards,	18	Mtr	



	lock strike-plate and shock absorbers as specified and applying a coat of approved steel primer after pretreatment of the surface as directed by Engineer-incharge: Profile C Fixing with adjustable lugs with split end tail to each jamb			
21	Providing and laying rectified Glazed Ceramic floor tiles of size 300x300 mm or more (thickness to be specified by the manufacturer), of 1st quality conforming to IS: 15622, of approved make, in colours White, Ivory, Grey, Fume Red Brown, laid on 20 mm thick cement mortar 1:4 (1 Cement: 4 Coarse sand), jointing with grey cement slurry @ 3.3 kg/ sqm including grouting the joints with white cement and matching pigments etc., complete.	10	Sqm	
22	Providing and fixing Ist quality ceramic glazed wall tiles conforming to IS: 15622 (thickness to be specified by the manufacturer), of approved make, in all colours, shades except burgundy, bottle green, black of any size as approved by Engineer-in-Charge, in skirting, risers of steps and dados, over 12 mm thick bed of cement mortar 1:3 (1 cement: 3 coarse sand) and jointing with grey cement slurry @ 3.3kg per sqm, including pointing in white cement mixed with pigment of matching shade complete.	22	Sqm	
23	Providing and fixing on wall face unplasticised Rigid PVC rain water pipes conforming to IS: 13592 Type A,	7	Mtr	



	including jointing with seal ring conforming to IS: 5382, leaving 10 mm gap for thermal expansion, (i) Single socketed pipes. 110 mm diameter			
24	Providing and fixing on wall face unplasticised - PVC moulded fittings/ accessories for unplasticised Rigid PVC rain water pipes conforming to IS: 13592 Type A, including jointing with seal ring conforming to IS: 5382, leaving 10 mm gap for thermal expansion			
Α.	Bend 87.5 degree 110 mm bend	2.000	EA	
B.	Shoe (Plain) 110 mm Shoe Qty;- 2 EA	2.000	EA	
25	Providing and fixing unplasticised -PVC pipe clips of approved design to unplasticised - PVC rain water pipes by means of 50x50x50 mm hard wood plugs, screwed with M.S. screws of required length, including cutting brick work and fixing in cement mortar 1:4 (1 cement : 4 coarse sand) and making good the wall etc. complete	6	EA	
26	12 mm cement plaster of mix : 1:6 (1 cement: 6 fine sand)	50.00	Sqm	
27	15 mm cement plaster on the rough side of single or half brick wall of mix 1:6 (1 cement: 6 fine sand)	60	Sqm	
28	6 mm cement plaster of mix : 1:3 (1 cement : 3 fine sand)	20	Sqm	
29	Distempering with 1st quality acrylic distemper (ready mixed) having VOC content less than 50gms/liter, of	70	Sqm	



	approved manufacturer, of required shade and colour complete, as per manufacturer's specification. Two or more coats on new work			
30	Finishing walls with Premium Acrylic Smooth exterior paint with Silicone additives of required shade: New work (Two or more coats applied @ 1.43 ltr/10 sqm over and including priming coat of exterior primer applied @ 2.20 kg/10 sqm).	60	Sqm	
31	Demolishing stone rubble masonry manually/ by mechanical means including stacking of serviceable material and disposal of unserviceable material within 50 metres lead as per direction of Engineer-in-charge	2	CUM	
32	Providing and fixing white vitreous china pedestal type water closet (European type W.C. pan) with seat and lid, 10 litre low level white P.V.C. flushing cistern, including flush pipe, with manually controlled device (handle lever), conforming to IS: 7231, with all fittings and fixtures complete, including cutting and making good the walls and floors wherever required: W.C. pan with ISI marked white solid plastic seat and lid	1	EA	
33	Providing and fixing water closet squatting pan (Indian type W.C. pan) with 100 mm sand cast Iron P or S trap, 10 litre low level white P.V.C. flushing cistern, including flush pipe, with manually controlled device (handle lever) conforming to IS: 7231, with all fittings and	1	EA	



	fixtures complete, including cutting and making good the walls and floors wherever required White Vitreous china Orissa pattern W.C. pan of size 580x440 mm with integral type foot rests			
34	Providing and fixing one piece construction white vitreous china squatting plate with an integral longitudinal flushing pipe, white P.V.C. automatic flushing cistern, with fittings, standard size G.I. / PVC flush pipe for back and front flush with standard spreader pipes with fittings, G.I clamps and C.P. brass coupling complete, including painting of fittings and cutting and making good the walls and floors etc. wherever required: Range of two squatting plates with 5 litre P.V.C. automatic flushing cistern	1	EA	
35	Providing and fixing wash basin with C.I. brackets, 15 mm C.P. brass pillar taps, 32 mm C.P. brass waste of standard pattern, including painting of fittings and brackets, cutting and making good the walls wherever require: White Vitreous China Washbasin size of 630x450mm with a single 15 mm C.P. brass pillar tap	2	EA	
36	Providing and fixing 600x450 mm beveled edge mirror of superior glass (of approved quality) complete with 6 mm thick hard board ground fixed to wooden cleats with C.P. brass screws and washers complete	1.000	EA	



37	Providing and fixing mirror of superior glass (of approved quality) and of required shape and size with plastic moulded frame of approved make and shade with 6 mm thick hard board backing Rectangular shape 1500x450 mm	2.000	EA	
38	Providing and fixing soil, waste and vent pipes 100 mm dia Hubless centrifugally cast (spun) iron pipes epoxy coated inside & outside IS:15905	10	Mtr	
39	Providing and fixing plain bend of required degree 100 mm dia Hubless centrifugally cast (spun) iron pipes epoxy coated inside & outside IS:15905	3.000	EA	
40	Providing and fixing terminal guard: 100 mm dia Hubless centrifugally cast (spun) iron pipes epoxy coated inside & outside IS:15905	1.000	EA	
41	Providing and fixing shielded coupling for Hubless centrifugally cast iron pipe 100 mm dia Hubless centrifugally cast (spun) iron pipes epoxy coated inside & outside IS:15905	10.000	EA	
42	Providing and fixing trap of self cleansing design with screwed down or hinged grating with or without vent arm complete, including cost of cutting and making good the walls and floors: 100 mm inlet and 100 mm outlet Hubless centrifugally cast	2.000	EA	



	(spun) iron epoxy coated inside & outside as per IS:15905			
43	Providing and fixing Chlorinated Polyvinyl Chloride (CPVC) pipes, having thermal stability for hot & cold water supply, including all CPVC plain & brass threaded fittings, i/c fixing the pipe with clamps at 1.00 m spacing. This includes jointing of pipes & fittings with one step CPVC solvent cement and the cost of cutting chases and making good the same including testing of joints complete as per direction of Engineer in Charge. Concealed work, including cutting chases and making good the walls etc. 15 mm nominal dia Pipes	1.000	Mtr	
44	Providing and fixing Chlorinated Polyvinyl Chloride (CPVC) pipes, having thermal stability for hot & cold water supply including all CPVC plain & brass threaded fittings This includes jointing of pipes & fittings with one step CPVC solvent cement, trenching, refilling & testing of joints omplete as per direction of Engineer in Charge. External work 20 mm nominal dia Pipes	15	Mtr	
45	Providing and placing on terrace (at all floor levels) polyethylene water storage tank, IS: 12701 marked, with cover and suitable locking arrangement and making necessary holes for inlet, outlet and overflow pipes but without fittings and the base support for tank	1000	Ltr	
46	Providing and fixing C.P. brass bib cock of approved quality conforming to IS:8931 : 15	4.000	EA	



	mm nominal bore				
47	Providing and fixing C.P. brass angle valve for basin mixer and geyser points of approved quality conforming to IS:8931 15 mm nominal bore	2.000	EA		
48	Providing and fixing C.P. Brass extension nipple (size 15mmx50mm) of approved make and quality as per direction of Engineer-incharge	4.000	EA		
49	Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/appropriate Z sections and other sections of approved make conforming to IS: 733 and IS: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/ neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing / paneling, C.P. brass / stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge. (Glazing, paneling and dash fasteners to be paid for separately):				
	A. For fixed portion Polyester powder coated aluminium (minimum thickness of polyester powder coating 50 micron) Qty:-60 KG	60	Kg		
<u> </u>		[58]		1	<u>l</u>



	B. For shutters of doors, windows & ventilators including providing and fixing hinges/ pivots and making provision for fixing of fittings wherever required including the cost of EPDM rubber / neoprene gasket required (Fittings shall be paid for separately) Polyester powder coated aluminium (minimum thickness of polyester powder coating 50 micron) Qty:-20 KG	20	Kg	
50	Providing and fixing glazing in aluminium door, window, ventilator shutters and partitions etc. with EPDM rubber / neoprene gasket etc. complete as per the architectural drawings and the directions of engineer-incharge. (Cost of aluminium snap beading shall be paid in basic item):			
A.	With float glass panes of 4.0 mm thickness (weight not less than 10kg/sqm)	4	Sqm	
B.	With float glass panes of 8 mm thickness (weight not less than 20 kg/sqm) Qty:- 10 Sqm	10	Sqm	
51	Providing and fixing factory made single extruded WPC (Wood Polymer Composite) solid door/window/ Ceosetory windows & other Frames/Chowkhat comprising of virgin PVC polymer of K value 58-60 (Suspension Grade), calcium carbonate and natural fibers (wood powder/ rice husk/wheat husk) and non toxic additives (maximum toxicity index of 12 for 100 gms) fabricated with miter joints after applying PVC solvent cement and screwed with full body	10	Mtr	



screws having minimum frame density of 750 kg/ cum, screw withdrawal strength of 2200 N (Face) & 1100 N (Edge), minimum compressive strength of 58 N/mm2, modulus of elasticity 900 N/mm2 and resistance to spread of flame of Class A category with property of being termite/borer proof, water/moisture proof and fire retardant and fixed in position with M.S hold fast/lugs/SS dash fasteners of required dia and length complete as per direction of Engineer-In-Charge. (M.S hold fast/lugs or SS dash fasteners shall be paid for separately). Note: For WPC solid door/window frames, minus 5mm tolerance in dimensions i.e depth and width of profile shall be acceptable. Variation in profile dimensions on plus side shall be acceptable but no extra payment on this account shall be made. Frame size 65 x 100 mm 52 Providing and fixing factory made single extruded WPC (Wood Polymer Composite) solid plain flush door shutter of required size comprising of virgin polymer of K value 58-60 (Suspension Grade), calcium carbonate and natural fibers (wood powder/ rice husk/wheat husk) and non toxic additives (maximum toxicity index of 12 for 100 gms) having minimum density of 650 kg/cum and screw withdrawal strength of 1800 N (Face) & 900 N (Edge), minimum compressive strength 50 N/mm2, modulus of elasticity 850 N/mm2 and resistance to spread of flame of Class A category with		threaded star headed SS				
frame density of 750 kg/ cum, screw withdrawal strength of 2200 N (Face) & 1100 N (Edge), minimum compressive strength of 58 N/mm2, modulus of elasticity 900 N/mm2 and resistance to spread of flame of Class A category with property of being termite/borer proof, water/moisture proof and fire retardant and fixed in position with M.S hold fast/lugs/SS dash fasteners of required dia and length complete as per direction of Engineer-In-Charge. (M.S hold fast/lugs or SS dash fasteners shall be paid for separately). Note: For WPC solid door/window frames, minus 5mm tolerance in dimensions i.e depth and width of profile shall be acceptable. Variation in profile dimensions on plus side shall be acceptable but no extra payment on this account shall be made. Frame size 65 x 100 mm 52 Providing and fixing factory made single extruded WPC (Wood Polymer Composite) solid plain flush door shutter of required size comprising of virgin polymer of K value 58-60 (Suspension Grade), calcium carbonate and natural fibers (wood powder/ rice husk/wheat husk) and non toxic additives (maximum toxicity index of 12 for 100 gms) having minimum density of 650 kg/cum and screw withdrawal strength of 1800 N (Face) & 900 N (Edge), minimum compressive strength 50 N/mm2, and duls of elasticity 850 N/mm2 and resistance to spread of flame of Class A category with						
screw withdrawal strength of 2200 N (Face) & 1100 N (Edge), minimum compressive strength of 58 N/mm2, modulus of elasticity 900 N/mm2 and resistance to spread of flame of Class A category with property of being termite/borer proof, water/moisture proof and fire retardant and fixed in position with M.S hold fast/lugs/SS dash fasteners of required dia and length complete as per direction of Engineer-In-Charge, (M.S hold fast/lugs or SS dash fasteners shall be paid for separately). Note: For WPC solid door/window frames, minus Smm tolerance in dimensions i.e depth and width of profile shall be acceptable. Variation in profile dimensions on plus side shall be acceptable but no extra payment on this account shall be made. Frame size 65 x 100 mm 52 Providing and fixing factory made single extruded WPC (Wood Polymer Composite) solid plain flush door shutter of required size comprising of virgin polymer of K value 58-60 (Suspension Grade), calcium carbonate and natural fibers (wood powder/ rice husk/wheat husk) and non toxic additives (maximum toxicity index of 12 for 100 gms) having minimum density of 650 kg/cum and screw withdrawal strength of 1800 N (Face) & 900 N (Edge), minimum compressive strength 50 N/mm2, modulus of elasticity 850 N/mm2 and resistance to spread of flame of Class A category with						
(Edge), minimum compressive strength of 58 N/mm2, modulus of elasticity 900 N/mm2 and resistance to spread of flame of Class A category with property of being termite/borer proof, water/moisture proof and fire retardant and fixed in position with M.S hold fast/lugs/SS dash fasteners of required dia and length complete as per direction of Engineer-In- Charge. (M.S hold fast/lugs or SS dash fasteners shall be paid for separately). Note: For WPC solid door/window frames, minus 5mm tolerance in dimensions i.e depth and width of profile shall be acceptable. Variation in profile dimensions on plus side shall be acceptable but no extra payment on this account shall be made. Frame size 65 x 100 mm 52 Providing and fixing factory made single extruded WPC (Wood Polymer Composite) solid plain flush door shutter of required size comprising of virgin polymer of K value 58- 60 (Suspension Grade), calcium carbonate and natural fibers (wood powder/ rice husk/wheat husk) and non toxic additives (maximum toxicity index of 12 for 100 gms) having minimum density of 650 kg/cum and screw withdrawal strength of 1800 N (Face) & 900 N (Edge), minimum compressive strength 50 N/mm2, and resistance to spread of flame of Class A category with						
(Edge), minimum compressive strength of 58 N/mm2, modulus of elasticity 900 N/mm2 and resistance to spread of flame of Class A category with property of being termite/borer proof, water/moisture proof and fire retardant and fixed in position with M.S hold fast/lugs/SS dash fasteners of required dia and length complete as per direction of Engineer-In-Charge. (M.S hold fast/lugs or SS dash fasteners shall be paid for separately). Note: For WPC solid door/window frames, minus 5mm tolerance in dimensions i.e depth and width of profile shall be acceptable. Variation in profile dimensions on plus side shall be acceptable but no extra payment on this account shall be made. Frame size 65 x 100 mm 52 Providing and fixing factory made single extruded WPC (Wood Polymer Composite) solid plain flush door shutter of required size comprising of virgin polymer of K value 58-60 (Suspension Grade), calcium carbonate and natural fibers (wood powder/ rice husk/wheat husk) and non toxic additives (maximum toxicity index of 12 for 100 gms) having minimum density of 650 kg/cum and screw withdrawal strength of 1800 N (Face) & 900 N (Edge), minimum compressive strength 50 N/mm2, modulus of elasticity 850 N/mm2, and resistance to spread of flame of Class A category with		_				
compressive strength of 58 N/mm2, modulus of elasticity 900 N/mm2 and resistance to spread of flame of Class A category with property of being termite/borer proof, water/moisture proof and fire retardant and fixed in position with M.S hold fast/lugs/SS dash fasteners of required dia and length complete as per direction of Engineer-In- Charge. (M.S hold fast/lugs or SS dash fasteners shall be paid for separately). Note: For WPC solid door/window frames, minus 5mm tolerance in dimensions i.e depth and width of profile shall be acceptable. Variation in profile dimensions on plus side shall be acceptable but no extra payment on this account shall be made. Frame size 65 x 100 mm 52 Providing and fixing factory made single extruded WPC (Wood Polymer Composite) solid plain flush door shutter of required size comprising of virgin polymer of K value 58- 60 (Suspension Grade), calcium carbonate and natural fibers (wood powder/ rice husk/wheat husk) and non toxic additives (maximum toxicity index of 12 for 100 gms) having minimum density of 650 kg/cum and screw withdrawal strength of 1800 N (Face) & 900 N (Edge), minimum compressive strength 50 N/mm2, modulus of elasticity 850 N/mm2 and resistance to spread of flame of Class A category with		2200 N (Face) & 1100 N				
compressive strength of 58 N/mm2, modulus of elasticity 900 N/mm2 and resistance to spread of flame of Class A category with property of being termite/borer proof, water/moisture proof and fire retardant and fixed in position with M.S hold fast/lugs/SS dash fasteners of required dia and length complete as per direction of Engineer-In- Charge. (M.S hold fast/lugs or SS dash fasteners shall be paid for separately). Note: For WPC solid door/window frames, minus 5mm tolerance in dimensions i.e depth and width of profile shall be acceptable. Variation in profile dimensions on plus side shall be acceptable but no extra payment on this account shall be made. Frame size 65 x 100 mm 52 Providing and fixing factory made single extruded WPC (Wood Polymer Composite) solid plain flush door shutter of required size comprising of virgin polymer of K value 58- 60 (Suspension Grade), calcium carbonate and natural fibers (wood powder/ rice husk/wheat husk) and non toxic additives (maximum toxicity index of 12 for 100 gms) having minimum density of 650 kg/cum and screw withdrawal strength of 1800 N (Face) & 900 N (Edge), minimum compressive strength 50 N/mm2, modulus of elasticity 850 N/mm2 and resistance to spread of flame of Class A category with		(Edge), minimum				
N/mm2, modulus of elasticity 900 N/mm2 and resistance to spread of flame of Class A category with property of being termite/borer proof, water/moisture proof and fire retardant and fixed in position with M.S hold fast/lugs/SS dash fasteners of required dia and length complete as per direction of Engineer-In-Charge. (M.S hold fast/lugs or SS dash fasteners shall be paid for separately). Note: For WPC solid door/window frames, minus 5mm tolerance in dimensions i.e depth and width of profile shall be acceptable. Variation in profile dimensions on plus side shall be acceptable but no extra payment on this account shall be made. Frame size 65 x 100 mm 52 Providing and fixing factory made single extruded WPC (Wood Polymer Composite) solid plain flush door shutter of required size comprising of virgin polymer of K value 58-60 (Suspension Grade), calcium carbonate and natural fibers (wood powder/ rice husk/wheat husk) and non toxic additives (maximum toxicity index of 12 for 100 gms) having minimum density of 650 kg/cum and screw withdrawal strength of 1800 N (Face) & 900 N (Edge), minimum compressive strength 50 N/mm2, modulus of elasticity 850 N/mm2 and resistance to spread of flame of Class A category with		compressive strength of 58				
900 N/mm2 and resistance to spread of flame of Class A category with property of being termite/borer proof, water/moisture proof and fire retardant and fixed in position with M.S hold fast/lugs/SS dash fasteners of required dia and length complete as per direction of Engineer-In-Charge. (M.S hold fast/lugs or SS dash fasteners shall be paid for separately). Note: For WPC solid door/window frames, minus 5mm tolerance in dimensions i.e depth and width of profile shall be acceptable. Variation in profile dimensions on plus side shall be acceptable but no extra payment on this account shall be made. Frame size 65 x 100 mm 52 Providing and fixing factory made single extruded WPC (Wood Polymer Composite) solid plain flush door shutter of required size comprising of virign polymer of K value 58-60 (Suspension Grade), calcium carbonate and natural fibers (wood powder/ rice husk/wheat husk) and non toxic additives (maximum toxicity index of 12 for 100 gms) having minimum density of 650 kg/cum and screw withdrawal strength of 1800 N (Face) & 900 N (Edge), minimum compressive strength 50 N/mm2, modulus of elasticity 850 N/mm2, modulus of elasticity 850 N/mm2, modulus of elasticity 850 N/mm2, modulus of class A category with						
spread of flame of Class A category with property of being termite/borer proof, water/moisture proof and fire retardant and fixed in position with M.S hold fast/lugs/SS dash fasteners of required dia and length complete as per direction of Engineer-In- Charge. (M.S hold fast/lugs or SS dash fasteners shall be paid for separately). Note: For WPC solid door/window frames, minus 5mm tolerance in dimensions i.e depth and width of profile shall be acceptable. Variation in profile dimensions on plus side shall be acceptable but no extra payment on this account shall be made. Frame size 65 x 100 mm 52 Providing and fixing factory made single extruded WPC (Wood Polymer Composite) solid plain flush door shutter of required size comprising of virgin polymer of K value 58- 60 (Suspension Grade), calcium carbonate and natural fibers (wood powder/ rice husk/wheat husk) and non toxic additives (maximum toxicity index of 12 for 100 gms) having minimum density of 650 kg/cum and screw withdrawal strength of 1800 N (Face) & 900 N (Edge), minimum compressive strength 50 N/mm2, modulus of elasticity 850 N/mm2 and resistance to spread of flame of Class A category with						
category with property of being termite/borer proof, water/moisture proof and fire retardant and fixed in position with M.S hold fast/lugs/SS dash fasteners of required dia and length complete as per direction of Engineer-In-Charge. (M.S hold fast/lugs or SS dash fasteners shall be paid for separately). Note: For WPC solid door/window frames, minus 5mm tolerance in dimensions i.e depth and width of profile shall be acceptable. Variation in profile dimensions on plus side shall be acceptable but no extra payment on this account shall be made. Frame size 65 x 100 mm 52 Providing and fixing factory made single extruded WPC (Wood Polymer Composite) solid plain flush door shutter of required size comprising of virgin polymer of K value 58-60 (Suspension Grade), calcium carbonate and natural fibers (wood powder/ rice husk/wheat husk) and non toxic additives (maximum toxicity index of 12 for 100 gms) having minimum density of 650 kg/cum and screw withdrawal strength of 1800 N (Face) & 900 N (Edge), minimum compressive strength 50 N/mm2, modulus of elasticity 850 N/mm2 and resistance to spread of flame of Class A category with						
being termite/borer proof, water/moisture proof and fire retardant and fixed in position with M.S hold fast/lugs/SS dash fasteners of required dia and length complete as per direction of Engineer-In- Charge. (M.S hold fast/lugs or SS dash fasteners shall be paid for separately). Note: For WPC solid door/window frames, minus 5mm tolerance in dimensions i.e depth and width of profile shall be acceptable. Variation in profile dimensions on plus side shall be acceptable but no extra payment on this account shall be made. Frame size 65 x 100 mm 52 Providing and fixing factory made single extruded WPC (Wood Polymer Composite) solid plain flush door shutter of required size comprising of virgin polymer of K value 58- 60 (Suspension Grade), calcium carbonate and natural fibers (wood powder/ rice husk/wheat husk) and non toxic additives (maximum toxicity index of 12 for 100 gms) having minimum density of 650 kg/cum and screw withdrawal strength of 1800 N (Face) & 900 N (Edge), minimum compressive strength 50 N/mm2, modulus of elasticity 850 N/mm2 and resistance to spread of flame of Class A category with		•				
water/moisture proof and fire retardant and fixed in position with M.S hold fast/lugs/SS dash fasteners of required dia and length complete as per direction of Engineer-In-Charge. (M.S hold fast/lugs or SS dash fasteners shall be paid for separately). Note: For WPC solid door/window frames, minus 5mm tolerance in dimensions i.e depth and width of profile shall be acceptable. Variation in profile dimensions on plus side shall be acceptable but no extra payment on this account shall be made. Frame size 65 x 100 mm 52 Providing and fixing factory made single extruded WPC (Wood Polymer Composite) solid plain flush door shutter of required size comprising of virgin polymer of K value 58-60 (Suspension Grade), calcium carbonate and natural fibers (wood powder/ rice husk/wheat husk) and non toxic additives (maximum toxicity index of 12 for 100 gms) having minimum density of 650 kg/cum and screw withdrawal strength of 1800 N (Face) & 900 N (Edge), minimum compressive strength 50 N/mm2, modulus of elasticity 850 N/mm2 and resistance to spread of flame of Class A category with						
retardant and fixed in position with M.S hold fast/lugs/SS dash fasteners of required dia and length complete as per direction of Engineer-In-Charge. (M.S hold fast/lugs or SS dash fasteners shall be paid for separately). Note: For WPC solid door/window frames, minus 5mm tolerance in dimensions i.e depth and width of profile shall be acceptable. Variation in profile dimensions on plus side shall be acceptable but no extra payment on this account shall be made. Frame size 65 x 100 mm 52 Providing and fixing factory made single extruded WPC (Wood Polymer Composite) solid plain flush door shutter of required size comprising of virgin polymer of K value 58-60 (Suspension Grade), calcium carbonate and natural fibers (wood powder/ rice husk/wheat husk) and non toxic additives (maximum toxicity index of 12 for 100 gms) having minimum density of 650 kg/cum and screw withdrawal strength of 1800 N (Face) & 900 N (Edge), minimum compressive strength 50 N/mm2, modulus of elasticity 850 N/mm2 and resistance to spread of flame of Class A category with		•				
with M.S hold fast/lugs/SS dash fasteners of required dia and length complete as per direction of Engineer-In- Charge. (M.S hold fast/lugs or SS dash fasteners shall be paid for separately). Note: For WPC solid door/window frames, minus 5mm tolerance in dimensions i.e depth and width of profile shall be acceptable. Variation in profile dimensions on plus side shall be acceptable but no extra payment on this account shall be made. Frame size 65 x 100 mm 52 Providing and fixing factory made single extruded WPC (Wood Polymer Composite) solid plain flush door shutter of required size comprising of virgin polymer of K value 58- 60 (Suspension Grade), calcium carbonate and natural fibers (wood powder/ rice husk/wheat husk) and non toxic additives (maximum toxicity index of 12 for 100 gms) having minimum density of 650 kg/cum and screw withdrawal strength of 1800 N (Face) & 900 N (Edge), minimum compressive strength 50 N/mm2, modulus of elasticity 850 N/mm2 and resistance to spread of flame of Class A category with		•				
dash fasteners of required dia and length complete as per direction of Engineer-In-Charge. (M.S hold fast/lugs or SS dash fasteners shall be paid for separately). Note: For WPC solid door/window frames, minus 5mm tolerance in dimensions i.e depth and width of profile shall be acceptable. Variation in profile dimensions on plus side shall be acceptable but no extra payment on this account shall be made. Frame size 65 x 100 mm 52 Providing and fixing factory made single extruded WPC (Wood Polymer Composite) solid plain flush door shutter of required size comprising of virgin polymer of K value 58-60 (Suspension Grade), calcium carbonate and natural fibers (wood powder/ rice husk/wheat husk) and non toxic additives (maximum toxicity index of 12 for 100 gms) having minimum density of 650 kg/cum and screw withdrawal strength of 1800 N (Face) & 900 N (Edge), minimum compressive strength 50 N/mm2, modulus of elasticity 850 N/mm2 and resistance to spread of flame of Class A category with		•				
and length complete as per direction of Engineer-In-Charge. (M.S hold fast/lugs or SS dash fasteners shall be paid for separately). Note: For WPC solid door/window frames, minus 5mm tolerance in dimensions i.e depth and width of profile shall be acceptable. Variation in profile dimensions on plus side shall be acceptable but no extra payment on this account shall be made. Frame size 65 x 100 mm 52 Providing and fixing factory made single extruded WPC (Wood Polymer Composite) solid plain flush door shutter of required size comprising of virgin polymer of K value 58-60 (Suspension Grade), calcium carbonate and natural fibers (wood powder/ rice husk/wheat husk) and non toxic additives (maximum toxicity index of 12 for 100 gms) having minimum density of 650 kg/cum and screw withdrawal strength of 1800 N (Face) & 900 N (Edge), minimum compressive strength 50 N/mm2, modulus of elasticity 850 N/mm2 and resistance to spread of flame of Class A category with		with M.S hold fast/lugs/SS				
direction of Engineer-In- Charge. (M.S hold fast/lugs or SS dash fasteners shall be paid for separately). Note: For WPC solid door/window frames, minus 5mm tolerance in dimensions i.e depth and width of profile shall be acceptable. Variation in profile dimensions on plus side shall be acceptable but no extra payment on this account shall be made. Frame size 65 x 100 mm 52 Providing and fixing factory made single extruded WPC (Wood Polymer Composite) solid plain flush door shutter of required size comprising of virgin polymer of K value 58-60 (Suspension Grade), calcium carbonate and natural fibers (wood powder/ rice husk/wheat husk) and non toxic additives (maximum toxicity index of 12 for 100 gms) having minimum density of 650 kg/cum and screw withdrawal strength of 1800 N (Face) & 900 N (Edge), minimum compressive strength 50 N/mm2, modulus of elasticity 850 N/mm2, modulus of elasticity 850 N/mm2, modulus of elasticity 850 N/mm2, modulus of class A category with		dash fasteners of required dia				
direction of Engineer-In- Charge. (M.S hold fast/lugs or SS dash fasteners shall be paid for separately). Note: For WPC solid door/window frames, minus 5mm tolerance in dimensions i.e depth and width of profile shall be acceptable. Variation in profile dimensions on plus side shall be acceptable but no extra payment on this account shall be made. Frame size 65 x 100 mm 52 Providing and fixing factory made single extruded WPC (Wood Polymer Composite) solid plain flush door shutter of required size comprising of virgin polymer of K value 58-60 (Suspension Grade), calcium carbonate and natural fibers (wood powder/ rice husk/wheat husk) and non toxic additives (maximum toxicity index of 12 for 100 gms) having minimum density of 650 kg/cum and screw withdrawal strength of 1800 N (Face) & 900 N (Edge), minimum compressive strength 50 N/mm2, modulus of elasticity 850 N/mm2, modulus of elasticity 850 N/mm2, modulus of elasticity 850 N/mm2, modulus of class A category with						
Charge. (M.S hold fast/lugs or SS dash fasteners shall be paid for separately). Note: For WPC solid door/window frames, minus 5mm tolerance in dimensions i.e depth and width of profile shall be acceptable. Variation in profile dimensions on plus side shall be acceptable but no extra payment on this account shall be made. Frame size 65 x 100 mm 52 Providing and fixing factory made single extruded WPC (Wood Polymer Composite) solid plain flush door shutter of required size comprising of virgin polymer of K value 58-60 (Suspension Grade), calcium carbonate and natural fibers (wood powder/ rice husk/wheat husk) and non toxic additives (maximum toxicity index of 12 for 100 gms) having minimum density of 650 kg/cum and screw withdrawal strength of 1800 N (Face) & 900 N (Edge), minimum compressive strength 50 N/mm2, modulus of elasticity 850 N/mm2, modulus of elasticity 850 N/mm2, modulus of elasticity so N/mm2 and resistance to spread of flame of Class A category with						
SS dash fasteners shall be paid for separately). Note: For WPC solid door/window frames, minus 5mm tolerance in dimensions i.e depth and width of profile shall be acceptable. Variation in profile dimensions on plus side shall be acceptable but no extra payment on this account shall be made. Frame size 65 x 100 mm 52 Providing and fixing factory made single extruded WPC (Wood Polymer Composite) solid plain flush door shutter of required size comprising of virgin polymer of K value 58-60 (Suspension Grade), calcium carbonate and natural fibers (wood powder/rice husk/wheat husk) and non toxic additives (maximum toxicity index of 12 for 100 gms) having minimum density of 650 kg/cum and screw withdrawal strength of 1800 N (Face) & 900 N (Edge), minimum compressive strength 50 N/mm2, modulus of elasticity 850 N/mm2 and resistance to spread of flame of Class A category with						
paid for separately). Note: For WPC solid door/window frames, minus 5mm tolerance in dimensions i.e depth and width of profile shall be acceptable. Variation in profile dimensions on plus side shall be acceptable but no extra payment on this account shall be made. Frame size 65 x 100 mm 52 Providing and fixing factory made single extruded WPC (Wood Polymer Composite) solid plain flush door shutter of required size comprising of virgin polymer of K value 58- 60 (Suspension Grade), calcium carbonate and natural fibers (wood powder/ rice husk/wheat husk) and non toxic additives (maximum toxicity index of 12 for 100 gms) having minimum density of 650 kg/cum and screw withdrawal strength of 1800 N (Face) & 900 N (Edge), minimum compressive strength 50 N/mm2, modulus of elasticity 850 N/mm2 and resistance to spread of flame of Class A category with						
For WPC solid door/window frames, minus 5mm tolerance in dimensions i.e depth and width of profile shall be acceptable. Variation in profile dimensions on plus side shall be acceptable but no extra payment on this account shall be made. Frame size 65 x 100 mm 52 Providing and fixing factory made single extruded WPC (Wood Polymer Composite) solid plain flush door shutter of required size comprising of virgin polymer of K value 58-60 (Suspension Grade), calcium carbonate and natural fibers (wood powder/ rice husk/wheat husk) and non toxic additives (maximum toxicity index of 12 for 100 gms) having minimum density of 650 kg/cum and screw withdrawal strength of 1800 N (Face) & 900 N (Edge), minimum compressive strength 50 N/mm2 modulus of elasticity 850 N/mm2 and resistance to spread of flame of Class A category with						
frames, minus 5mm tolerance in dimensions i.e depth and width of profile shall be acceptable. Variation in profile dimensions on plus side shall be acceptable but no extra payment on this account shall be made. Frame size 65 x 100 mm 52 Providing and fixing factory made single extruded WPC (Wood Polymer Composite) solid plain flush door shutter of required size comprising of virgin polymer of K value 58-60 (Suspension Grade), calcium carbonate and natural fibers (wood powder/ rice husk/wheat husk) and non toxic additives (maximum toxicity index of 12 for 100 gms) having minimum density of 650 kg/cum and screw withdrawal strength of 1800 N (Face) & 900 N (Edge), minimum compressive strength 50 N/mm2, modulus of elasticity 850 N/mm2 and resistance to spread of flame of Class A category with		1,				
in dimensions i.e depth and width of profile shall be acceptable. Variation in profile dimensions on plus side shall be acceptable but no extra payment on this account shall be made. Frame size 65 x 100 mm 52 Providing and fixing factory made single extruded WPC (Wood Polymer Composite) solid plain flush door shutter of required size comprising of virgin polymer of K value 58-60 (Suspension Grade), calcium carbonate and natural fibers (wood powder/ rice husk/wheat husk) and non toxic additives (maximum toxicity index of 12 for 100 gms) having minimum density of 650 kg/cum and screw withdrawal strength of 1800 N (Face) & 900 N (Edge), minimum compressive strength 50 N/mm2, modulus of elasticity 850 N/mm2 and resistance to spread of flame of Class A category with						
width of profile shall be acceptable. Variation in profile dimensions on plus side shall be acceptable but no extra payment on this account shall be made. Frame size 65 x 100 mm 52 Providing and fixing factory made single extruded WPC (Wood Polymer Composite) solid plain flush door shutter of required size comprising of virgin polymer of K value 58-60 (Suspension Grade), calcium carbonate and natural fibers (wood powder/rice husk/wheat husk) and non toxic additives (maximum toxicity index of 12 for 100 gms) having minimum density of 650 kg/cum and screw withdrawal strength of 1800 N (Face) & 900 N (Edge), minimum compressive strength 50 N/mm2, modulus of elasticity 850 N/mm2 and resistance to spread of flame of Class A category with		•				
acceptable. Variation in profile dimensions on plus side shall be acceptable but no extra payment on this account shall be made. Frame size 65 x 100 mm 52 Providing and fixing factory made single extruded WPC (Wood Polymer Composite) solid plain flush door shutter of required size comprising of virgin polymer of K value 58-60 (Suspension Grade), calcium carbonate and natural fibers (wood powder/rice husk/wheat husk) and non toxic additives (maximum toxicity index of 12 for 100 gms) having minimum density of 650 kg/cum and screw withdrawal strength of 1800 N (Face) & 900 N (Edge), minimum compressive strength 50 N/mm2, modulus of elasticity 850 N/mm2 and resistance to spread of flame of Class A category with		•				
profile dimensions on plus side shall be acceptable but no extra payment on this account shall be made. Frame size 65 x 100 mm 52 Providing and fixing factory made single extruded WPC (Wood Polymer Composite) solid plain flush door shutter of required size comprising of virgin polymer of K value 58-60 (Suspension Grade), calcium carbonate and natural fibers (wood powder/ rice husk/wheat husk) and non toxic additives (maximum toxicity index of 12 for 100 gms) having minimum density of 650 kg/cum and screw withdrawal strength of 1800 N (Face) & 900 N (Edge), minimum compressive strength 50 N/mm2 and resistance to spread of flame of Class A category with		•				
side shall be acceptable but no extra payment on this account shall be made. Frame size 65 x 100 mm 52 Providing and fixing factory made single extruded WPC (Wood Polymer Composite) solid plain flush door shutter of required size comprising of virgin polymer of K value 58-60 (Suspension Grade), calcium carbonate and natural fibers (wood powder/ rice husk/wheat husk) and non toxic additives (maximum toxicity index of 12 for 100 gms) having minimum density of 650 kg/cum and screw withdrawal strength of 1800 N (Face) & 900 N (Edge), minimum compressive strength 50 N/mm2, modulus of elasticity 850 N/mm2 and resistance to spread of flame of Class A category with						
no extra payment on this account shall be made. Frame size 65 x 100 mm 52 Providing and fixing factory made single extruded WPC (Wood Polymer Composite) solid plain flush door shutter of required size comprising of virgin polymer of K value 58-60 (Suspension Grade), calcium carbonate and natural fibers (wood powder/rice husk/wheat husk) and non toxic additives (maximum toxicity index of 12 for 100 gms) having minimum density of 650 kg/cum and screw withdrawal strength of 1800 N (Face) & 900 N (Edge), minimum compressive strength 50 N/mm2, modulus of elasticity 850 N/mm2 and resistance to spread of flame of Class A category with		profile dimensions on plus				
account shall be made. Frame size 65 x 100 mm 52 Providing and fixing factory made single extruded WPC (Wood Polymer Composite) solid plain flush door shutter of required size comprising of virgin polymer of K value 58-60 (Suspension Grade), calcium carbonate and natural fibers (wood powder/rice husk/wheat husk) and non toxic additives (maximum toxicity index of 12 for 100 gms) having minimum density of 650 kg/cum and screw withdrawal strength of 1800 N (Face) & 900 N (Edge), minimum compressive strength 50 N/mm2, modulus of elasticity 850 N/mm2 and resistance to spread of flame of Class A category with		side shall be acceptable but				
account shall be made. Frame size 65 x 100 mm 52 Providing and fixing factory made single extruded WPC (Wood Polymer Composite) solid plain flush door shutter of required size comprising of virgin polymer of K value 58-60 (Suspension Grade), calcium carbonate and natural fibers (wood powder/rice husk/wheat husk) and non toxic additives (maximum toxicity index of 12 for 100 gms) having minimum density of 650 kg/cum and screw withdrawal strength of 1800 N (Face) & 900 N (Edge), minimum compressive strength 50 N/mm2, modulus of elasticity 850 N/mm2 and resistance to spread of flame of Class A category with		no extra payment on this				
be made. Frame size 65 x 100 mm 52 Providing and fixing factory made single extruded WPC (Wood Polymer Composite) solid plain flush door shutter of required size comprising of virgin polymer of K value 58-60 (Suspension Grade), calcium carbonate and natural fibers (wood powder/rice husk/wheat husk) and non toxic additives (maximum toxicity index of 12 for 100 gms) having minimum density of 650 kg/cum and screw withdrawal strength of 1800 N (Face) & 900 N (Edge), minimum compressive strength 50 N/mm2, modulus of elasticity 850 N/mm2 and resistance to spread of flame of Class A category with						
Frame size 65 x 100 mm 52 Providing and fixing factory made single extruded WPC (Wood Polymer Composite) solid plain flush door shutter of required size comprising of virgin polymer of K value 58-60 (Suspension Grade), calcium carbonate and natural fibers (wood powder/rice husk/wheat husk) and non toxic additives (maximum toxicity index of 12 for 100 gms) having minimum density of 650 kg/cum and screw withdrawal strength of 1800 N (Face) & 900 N (Edge), minimum compressive strength 50 N/mm2, modulus of elasticity 850 N/mm2 and resistance to spread of flame of Class A category with						
52 Providing and fixing factory made single extruded WPC (Wood Polymer Composite) solid plain flush door shutter of required size comprising of virgin polymer of K value 58-60 (Suspension Grade), calcium carbonate and natural fibers (wood powder/rice husk/wheat husk) and non toxic additives (maximum toxicity index of 12 for 100 gms) having minimum density of 650 kg/cum and screw withdrawal strength of 1800 N (Face) & 900 N (Edge), minimum compressive strength 50 N/mm2, modulus of elasticity 850 N/mm2 and resistance to spread of flame of Class A category with						
made single extruded WPC (Wood Polymer Composite) solid plain flush door shutter of required size comprising of virgin polymer of K value 58- 60 (Suspension Grade), calcium carbonate and natural fibers (wood powder/ rice husk/wheat husk) and non toxic additives (maximum toxicity index of 12 for 100 gms) having minimum density of 650 kg/cum and screw withdrawal strength of 1800 N (Face) & 900 N (Edge), minimum compressive strength 50 N/mm2, modulus of elasticity 850 N/mm2 and resistance to spread of flame of Class A category with		1 Tamo 3120 00 X 100 mm				
made single extruded WPC (Wood Polymer Composite) solid plain flush door shutter of required size comprising of virgin polymer of K value 58- 60 (Suspension Grade), calcium carbonate and natural fibers (wood powder/ rice husk/wheat husk) and non toxic additives (maximum toxicity index of 12 for 100 gms) having minimum density of 650 kg/cum and screw withdrawal strength of 1800 N (Face) & 900 N (Edge), minimum compressive strength 50 N/mm2, modulus of elasticity 850 N/mm2 and resistance to spread of flame of Class A category with	52	Providing and fixing factory		5	Sqm	
(Wood Polymer Composite) solid plain flush door shutter of required size comprising of virgin polymer of K value 58- 60 (Suspension Grade), calcium carbonate and natural fibers (wood powder/ rice husk/wheat husk) and non toxic additives (maximum toxicity index of 12 for 100 gms) having minimum density of 650 kg/cum and screw withdrawal strength of 1800 N (Face) & 900 N (Edge), minimum compressive strength 50 N/mm2, modulus of elasticity 850 N/mm2 and resistance to spread of flame of Class A category with					1	
solid plain flush door shutter of required size comprising of virgin polymer of K value 58- 60 (Suspension Grade), calcium carbonate and natural fibers (wood powder/ rice husk/wheat husk) and non toxic additives (maximum toxicity index of 12 for 100 gms) having minimum density of 650 kg/cum and screw withdrawal strength of 1800 N (Face) & 900 N (Edge), minimum compressive strength 50 N/mm2, modulus of elasticity 850 N/mm2 and resistance to spread of flame of Class A category with						
of required size comprising of virgin polymer of K value 58-60 (Suspension Grade), calcium carbonate and natural fibers (wood powder/rice husk/wheat husk) and non toxic additives (maximum toxicity index of 12 for 100 gms) having minimum density of 650 kg/cum and screw withdrawal strength of 1800 N (Face) & 900 N (Edge), minimum compressive strength 50 N/mm2, modulus of elasticity 850 N/mm2 and resistance to spread of flame of Class A category with		• • • • • • • • • • • • • • • • • • • •				
virgin polymer of K value 58- 60 (Suspension Grade), calcium carbonate and natural fibers (wood powder/ rice husk/wheat husk) and non toxic additives (maximum toxicity index of 12 for 100 gms) having minimum density of 650 kg/cum and screw withdrawal strength of 1800 N (Face) & 900 N (Edge), minimum compressive strength 50 N/mm2, modulus of elasticity 850 N/mm2 and resistance to spread of flame of Class A category with		•				
60 (Suspension Grade), calcium carbonate and natural fibers (wood powder/ rice husk/wheat husk) and non toxic additives (maximum toxicity index of 12 for 100 gms) having minimum density of 650 kg/cum and screw withdrawal strength of 1800 N (Face) & 900 N (Edge), minimum compressive strength 50 N/mm2, modulus of elasticity 850 N/mm2 and resistance to spread of flame of Class A category with						
calcium carbonate and natural fibers (wood powder/ rice husk/wheat husk) and non toxic additives (maximum toxicity index of 12 for 100 gms) having minimum density of 650 kg/cum and screw withdrawal strength of 1800 N (Face) & 900 N (Edge), minimum compressive strength 50 N/mm2, modulus of elasticity 850 N/mm2 and resistance to spread of flame of Class A category with						
natural fibers (wood powder/ rice husk/wheat husk) and non toxic additives (maximum toxicity index of 12 for 100 gms) having minimum density of 650 kg/cum and screw withdrawal strength of 1800 N (Face) & 900 N (Edge), minimum compressive strength 50 N/mm2, modulus of elasticity 850 N/mm2 and resistance to spread of flame of Class A category with						
rice husk/wheat husk) and non toxic additives (maximum toxicity index of 12 for 100 gms) having minimum density of 650 kg/cum and screw withdrawal strength of 1800 N (Face) & 900 N (Edge), minimum compressive strength 50 N/mm2, modulus of elasticity 850 N/mm2 and resistance to spread of flame of Class A category with						
non toxic additives (maximum toxicity index of 12 for 100 gms) having minimum density of 650 kg/cum and screw withdrawal strength of 1800 N (Face) & 900 N (Edge), minimum compressive strength 50 N/mm2, modulus of elasticity 850 N/mm2 and resistance to spread of flame of Class A category with		•				
toxicity index of 12 for 100 gms) having minimum density of 650 kg/cum and screw withdrawal strength of 1800 N (Face) & 900 N (Edge), minimum compressive strength 50 N/mm2, modulus of elasticity 850 N/mm2 and resistance to spread of flame of Class A category with		,				
gms) having minimum density of 650 kg/cum and screw withdrawal strength of 1800 N (Face) & 900 N (Edge), minimum compressive strength 50 N/mm2, modulus of elasticity 850 N/mm2 and resistance to spread of flame of Class A category with		non toxic additives (maximum				
gms) having minimum density of 650 kg/cum and screw withdrawal strength of 1800 N (Face) & 900 N (Edge), minimum compressive strength 50 N/mm2, modulus of elasticity 850 N/mm2 and resistance to spread of flame of Class A category with		toxicity index of 12 for 100				
of 650 kg/cum and screw withdrawal strength of 1800 N (Face) & 900 N (Edge), minimum compressive strength 50 N/mm2, modulus of elasticity 850 N/mm2 and resistance to spread of flame of Class A category with		gms) having minimum density				
withdrawal strength of 1800 N (Face) & 900 N (Edge), minimum compressive strength 50 N/mm2, modulus of elasticity 850 N/mm2 and resistance to spread of flame of Class A category with		• •				
(Face) & 900 N (Edge), minimum compressive strength 50 N/mm2, modulus of elasticity 850 N/mm2 and resistance to spread of flame of Class A category with						
minimum compressive strength 50 N/mm2, modulus of elasticity 850 N/mm2 and resistance to spread of flame of Class A category with						
strength 50 N/mm2, modulus of elasticity 850 N/mm2 and resistance to spread of flame of Class A category with		, ,				
of elasticity 850 N/mm2 and resistance to spread of flame of Class A category with		•				
resistance to spread of flame of Class A category with						
of Class A category with						
[60]		or Class A category With	<u> </u>			



	property of being termite/borer proof, water/moisture proof and fire retardant and fixing with stainless steel butt hinges of required size with necessary full body threaded star headed counter sunk S.S screws, all as per direction of Engineer-In- Charge. (Note: stainless steel butt hinges and necessary S.S screws shall be paid separately) 35 mm thick			
53	Providing and fixing Swan Neck CP Brass pillar tap (IS 8931) of approved quality for ovel wash basin	3	EA	
54	Providing and fixing Stainless Steel grating of approved quality and colour Circular type-125mm nominal dia with 25mm waste hole	3	EA	
55	Boring providing and installing cast in situ single under reamed piles of specified diameter and length below pile cap in cement concrete 1:1.5:3 (1 cement : 1.5 coarse sand : 3 stone aggregate 20mm nominal size), to carry a safe working load not less than specified, excluding the cost of steel reinforcement but including the cost of boring with augar and the length of the pile to be embedded in pile cap etc. all complete. (Length of pile for payment shall be measured upto to the bottom of pile cap): 300 mm dia pile	30	Mtr	
56	Water proofing treatment in horizontal and vertical surface with water based	12	Sqm	



	polyurethane coating (PU) with ecofriendly properties. Preparation of the surface by using suitable means like grinding, treating the cracks by making V grooves and filling the groove by bituminous compound of approved makes, providing and applying primer coat of water based PU after diluting with 50% of water @ 0.30 Kg/Sqm or as per manufacturers specifications, providing and applying first coat of PU coating material @ 0.80 Kg/Sqm or as per manufacturers specification by brush/roller then providing and applying second coat of PU coating material @ 0.70080 kg/SPM or as per manufacturers specification, suitable interval between first and second coat should be kept as per manufacturers specification. Final layer developed after final coat should not be less than 1.5mm. the operation shall be carried out after scraping and properly cleaning the surface to remove loose particles with brushes complete in all respect as per direction of EIC. (The product performance shall carry guarantee for ten years against any leakage has to be insured by contractor 10% of amount will be withheld against this item)		NA4-	
57	Providing and laying non- pressure NP2 class (light duty) R.C.C. pipes with collars jointed with stiff mixture of cement mortar in the proportion of 1:2 (1 cement : 2 fine sand) including testing of joints etc. complete 150 mm dia. R.C.C. pipe	[62]	Mtr	



58	Constructing brick masonry manhole in cement mortar 1:4 (1cement: 4 coarse sand) with R.C.C. top slab with 1:1.5:3 mix (1 cement: 1.5 coarse sand (zone-III): 3 graded stone aggregate 20 mm nominal size), foundation concrete 1:4:8 mix (1 cement: 4 coarse sand (zone-III): 8 graded stone aggregate 40 mm nominal size), inside plastering 12 mm thick with cement mortar 1:3 (1 cement: 3 coarse sand) finished with floating coat of neat cement and making channels in cement concrete 1:2:4 (1 cement: 2 coarse sand: 4 graded stone aggregate 20 mm nominal size) finished with a floating coat of neat cement complete as per standard design: Inside size 90x80 cm and 60 cm deep including C.I. cover with frame (light duty) 455x610 mm internal dimensions, total weight of cover and frame to be not less than 38 kg (weight of cover 23 kg and weight of frame 15 kg): With common burnt clay F.P.S. (non modular) bricks of class designation 7.5	1	EA	
59	Providing and fixing G.I. pipes complete with G.I. fittings and clamps, i/c cutting and making good the walls etc. Exposed on wall-20 mm dia nominal bore	15	Mtr	
60	Removing white or colour wash by scrapping and sand papering and preparing the surface smooth including necessary repairs to scratches etc. complete	100	Sqm	
61	Providing and applying white cement based putty of	100	Sqm	



	average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and smooth complete.			
62	Finishing walls with Premium plastic acrylic emulsion of interior grade, having VOC content less than 50 grams/ litre. New work (Two or more coats applied @ 1.43 ltr/10 sqm over and including priming coat of exterior primer applied @ 2.20 kg/10 sqm)	100	Sqm	
Item No.20	Providing and Fixing 15 mm thick densified tegular edged eco-friendly light weight calcium silicate false ceiling tiles of approved texture of size 595 x 595 mm in true horizontal level, suspended on inter locking metal grid of hot dipped galvanised steel sections (galvanising @ 120 grams per sqm including both side) consisting of main 'T' runner suitably spaced at joints to get required length and of size 24x38 mm made from 0.33 mm thick (minimum) sheet, spaced 1200 mm centre to centre, and cross "T" of size 24x28 mm made out of 0.33 mm (Minimum) sheet, 1200 mm long spaced between main'T' at 600 mm centre to centre to form a grid of 1200x600 mm and secondary cross 'T' of length 600 mm and size 24 x28 mm made of 0.33 mm thick Minimum) sheet to be inter locked at middle of the 1200x 600 mm panel to from grid of size 600x600 mm, resting on periphery walls /partitions on a Perimeter wall angle pre-	33	Sqm	



64	of 0.40 mm thick (minimum) sheet with the help of rawl plugs at 450 mm centre to centre with 25 mm long dry wall screws @ 230 mm interval and laying 15 mm thick densified edges calicum silicate ceiling tiles of approved texture in the grid, including, cutting/ making opening for services like diffusers, grills, light fittings, fixtures, smoke detectors etc., wherever required. Main 'T' runners to be suspended from ceiling using G.I. slotted cleats of size 25x35x1.6 mm fixed to ceiling with 12.5 mm dia and 50 mm long dash fasteners, 4 mm G.I. adjustable rods with galvanised steel level clips of size 85 x 30 x 0.8 mm, spaced at 1200 mm centre to centre along main 'T', bottom exposed with 24 mm of all T sections shall be pre-painted with polyester baked paint, for all heights, as per specifications, drawings and as directed by Engineer-in-Charge. Only calcium silicate false ceiling area will be measured from wall to wall. No deduction shall be made for exposed frames/opening (cut outs) having area less than 0.30 sqm.The calcium silicate ceiling tile shall have NRC value of 0.50 (Minimum), light reflection > 85%, non-combustible as per B.S. 476 part IV, 100% humidity resistance and also having thermal conductivity <0.043 w/mK.			
65	Any other charges (if any)			
		[65]		



66	Total			
67	Total GST amount			
68	Total			
69	Total Price (F.O.R, SPM, NARMADAPURAM) (in figures only) (46+47)			
70	Total Price (F.O.R, SPM, NARMADAPURAM) (in words only)			

Note :-The method of evaluation of L1 criteria for awarding the contract shall be decided taking into consideration the total landed price up to SPM Narmadapuram.

Signature
Name
Designation
Date
Stamp of the Organization



ANNEXURE - II

TWO BID, SINGLE STAGE (TWO PACKET) TENDER BIDDER'S CHECK LIST BEFORE TENDER SUBMISSION

Part I: - TECHNO-COMMERCIAL BID

S.No.	Tender Submission Check Points	Check before submission Tick ()
1	Tender Fee	Not Applicable
2	Earnest Money Deposited	Applicable
4	Term of Delivery :- FOR, SPM Narmadapuram, duly unloaded	
5	Delivery Period: Acceptance of delivery period as per tender Document	
6	Tender Validity 120 days as per the tender	
7	Payment Terms as per the tender document.	
8	Accept the Warranty clause as per tender	
9	Technical Specification –Section VII as per tender	
10	Submit Manufacturer's Authorization form	
11	Consisting of all the Quality control requirements as per Section viii of the tender	
12	Submit the documents as per Qualification / Eligibility criteria – Section IX	
13	Blank Price Bid as per Section XI (Without Price but mention the taxes & other Other charges)	
14	Fill Tender Form – Section X duly seal & sign (Without mentioning price)	
15	Submit a document on letter head with seal and sign stating "unconditional accepting all the terms and conditions of tender enquiry without any deviations with acceptance of all section of this tender document (GIT, SIT, SCC, Quality Control requirement, Tender Form, Questionnaire etc.,)	

NOTE: "BIDDER TO FURNISH STIPULATED DOCUMENTS ALONG WITH TENDER IN SUPPORT OF FULFILLMENT OF TENDER CRITERIA. FURTHER CORRESPONDENCE IN THIS REGARD WILL NOT BE ENTERTAINED FOR ANY REASON. NON-SUBMISSION OR INCOMPLETE SUBMISSION OF DOCUMENTS MAY LEAD TO REJECTION OF OFFER

Part II: - PRICE BID

S.No	Tender Submission Check Points	Check before submission Tick ()
1	Price Bid as per Section XI (Price including all taxes & other charges)	

(Bidder's Seal & Sign) Seal & Sign)



<u>ANNEXURE – III</u>

Tender No. 6000017712/Civil/700 Dt. 27.08.2022 (To be submitted on the letter head)

DECLARATION

We do hereby declare that,

- 1. We have not been blacklisted /debarred by BNPMIPL /BRBNMPL /SPMCIL or any Govt. Departments for participation in tenders. The information provided above is correct and true to the best of my knowledge and belief.
- 2. We do hereby declare that we have read and understood all terms and conditions of tender document including GIT, SIT, GCC, SCC, Technical Specification, Quality Control Criteria and confirm to abide to those conditions without any counter conditions.
- 3. "We are accepting all the terms and conditions of the tender document without any deviation and withdraw all deviations if any"
- 4. "We Declare that If we withdraw or modify our bids during period of validity of tender etc. than we will

be suspended for the period of 03 years from the date of opening of tender."

Signature
Name
Designation
Date
Stamp of the Organization

Regd. Office: - 16th Floor, Jawahar Vyapar Bhawan, Janpath, New Delhi - 110001



ANNEXURE-IV

Tender No. 6000017712/Civil/700 Dated: 27.08.2022 (To be submitted on the letter head)

DECLARATION

"I have read the clause regarding restrictions on procurement from a bidder of a country which
shares a land border with India. I certify that M/s
(firm's name) is not from such a country or, if from such a country, has been registered
with the Competent Authority. I hereby certify that M/s
(firm's name) fulfils at requirements in this regard and is eligible to be considered."
(where applicable, evidence of valid registration by the competent Authority shall be attached)
I, the undersigned, declare that the itemoriginate in(Name
of the country).
Signature
Name
Designation
Date
Stamp of the
Organization



Annexure-V

Declaration for Section 206AB of TDS under income tax Act, 1961

(to be submitted on Letter Head)

Vendor Cod	de:					
M/s						
				GSTIN		
I/We			<	Legal Name a	nd complete addr	ess >,
PAN:		, т	TAN:, referring to the			
provisions of	of 206AB of the	e IT Act, 1961	, hereby declare th	e following:-		
Financia I Year	Aggregate TDS & TCS credit in our name was Rs. 50,000 or more ("Yes / No")	Income Tax Return ("ITR") Filed ("Yes/No")	E-filing Acknowledgme nt Number (15 digit - numeric) (Attach copy of acknowledgme nts)	139(1) (DD/MM/YYY	with Aadhaar number or will link it before 30 Jun 2021 (or	
2018-19						
2019-20						
correct, cor which are le indemnify S	mplete and is t	ruly stated. Ir on account o ne.	n case there is a ta	x liability, intere	of what is stated at st or penal consequi ion, I/we undertake	uences
Authorized	Signatory					
Date:						
Note: In ca	se the vendor	failed to com	ply with the above	provisions, TDS	S shall be deducted	at the

higher of the following rates, namely: -

- (i) at twice the rate specified in the relevant provision of the Act; or
- (ii) at twice the rate or rates in force; or
- (iii) at the rate of five per cent (5%).